

Easy Stagna LED

NEW EASY LED 36W-1200 IP65 4K

Beghelli Code: **75471**



Description: Lighting
EAN: 8002219906618

ELECTRICAL AND LIGHTING TECHNICAL CHARACTERISTIC

EQUIVALENT POWER: 2x36w
SUPPLY VOLTAGE TYPE: AC
NOMINAL VOLTAGE AC: 230 V
VOLTAGE SUPPLY RANGE AC: 220 V÷240 V
FREQUENCY SUPPLY RANGE: 50 Hz÷60 Hz
POWER FACTOR (Cos fi): 0.9
ABSORBED POWER: 36 W
FLUX: 5040 lm
EFFICIENCY: 140 lm/W
Ta: -20 °C÷40 °C
INSULATION CLASS: II
CRI: >80
CCT: 4000 K
COLOR CONSISTENCY (SDCM): SDCM2
LUMINOUS FLUX MAINTENANCE L70/B20: 71000 h
LUMINOUS FLUX MAINTENANCE L70/B50: 100000 h
LUMINOUS FLUX MAINTENANCE L80/B10: 45000 h
LUMINOUS FLUX MAINTENANCE L80/B20: 50000 h
LUMINOUS FLUX MAINTENANCE L80/B50: 62000 h
LUMINOUS FLUX MAINTENANCE L90/B10: 25000 h
LUMINOUS FLUX MAINTENANCE L90/B50: 29500 h
BEAM ANGLE: 140 °
DRIVER TYPE: For constant current LED
CURRENT SUPPLY AC: 150 mA

MOUNTING AND APPLICATIONS

MOUNTING: Ceiling
ENVIRONMENT: Indoor/Outdoor
APPLICATION: Offices / Production / Warehouses

MECHANICAL CHARACTERISTICS

Dimension: Height: 49 mm **Length:** 1200 mm **Width:** 68 mm
PRODUCT WEIGHT: 0.5 kg
BODY MATERIAL: COLOUR White RAL 9016
PROTECTION DEGREE: IP65
MECHANICAL IMPACTS PROTECTION DEGREE: IK06
QUANTITY PER BOX SINGLE/MULTIPLE/DELIVERY: 1/12/

CERTIFICATES AND STANDARDS

STANDARDS: UK SI 2021 No. 1095, EN 62471:2008, EN IEC 60598-1:2021, EN 60598-2-1:1989, EN IEC 63000:2018, EN 62493:2010, EN 61000-3-3:2013, REG. 2019/2020(EU), EN IEC 55015:2019 + A11:2020, EN IEC 61000-3-2 :2019, EN 60598-2-22:2014 + AC:2015 + AC:2016-05 + AC:2016-09 + A1:2020

