

# Easy Stagna LED



NEW EASY LED 18W-600 IP65 4K

Beghelli Code: **75470**



**Description:** Lighting

**EAN:** 8002219906595

## ELECTRICAL AND LIGHTING TECHNICAL CHARACTERISTIC

**EQUIVALENT POWER:** 2x18w

**SUPPLY VOLTAGE TYPE:** AC

**NOMINAL VOLTAGE AC:** 230 V

**VOLTAGE SUPPLY RANGE AC:** 220 V±240 V

**FREQUENCY SUPPLY RANGE:** 50 Hz±60 Hz

**POWER FACTOR (Cos fi):** 0.9

**ABSORBED POWER:** 18 W

**FLUX:** 2520 lm

**EFFICIENCY:** 140 lm/W

**Ta:** -20 °C±40 °C

**INSULATION CLASS:** II

**CRI:** >80

**CCT:** 4000 K

**COLOR CONSISTENCY (SDCM):** SDCM2

**LUMINOUS FLUX MAINTENANCE L70/B20:** 71000 h

**LUMINOUS FLUX MAINTENANCE L70/B50:** 100000 h

**LUMINOUS FLUX MAINTENANCE L80/B10:** 45000 h

**LUMINOUS FLUX MAINTENANCE L80/B20:** 50000 h

**LUMINOUS FLUX MAINTENANCE L80/B50:** 62000 h

**LUMINOUS FLUX MAINTENANCE L90/B10:** 25000 h

**LUMINOUS FLUX MAINTENANCE L90/B50:** 29500 h

**BEAM ANGLE:** 140 °

**DRIVER TYPE:** For constant current LED

**CURRENT SUPPLY AC:** 80 mA

## MOUNTING AND APPLICATIONS

**MOUNTING:** Ceiling

**ENVIRONMENT:** Indoor/Outdoor

**APPLICATION:** Offices / Production / Warehouses

## MECHANICAL CHARACTERISTICS

**Dimension: Height:** 49 mm **Length:** 600 mm **Width:** 68 mm

**PRODUCT WEIGHT:** 0.28 kg

**BODY MATERIAL: COLOUR** White RAL 9016

**PROTECTION DEGREE:** IP65

**MECHANICAL IMPACTS PROTECTION DEGREE:** IK06

**QUANTITY PER BOX SINGLE/MULTIPLE/DELIVERY:** 1/12/

## CERTIFICATES AND STANDARDS

**STANDARDS:** UK SI 2021 No. 1095, EN 62471:2008, EN IEC 60598-1:2021, EN 60598-2-1:1989, EN IEC 63000:2018, EN 62493:2010, EN 61000-3-3:2013, REG. 2019/2020(EU), EN IEC 55015:2019 + A11:2020, EN IEC 61000-3-2 :2019, EN 60598-2-22:2014 + AC:2015 + AC:2016-05 + AC:2016-09 + A1:2020

