

# Easy Stagna LED



NEW EASY LED 50W-1500 IP65 4K

Beghelli Code: **75472**



**Description:** Lighting  
**EAN:** 8002219906632

## ELECTRICAL AND LIGHTING TECHNICAL CHARACTERISTIC

**EQUIVALENT POWER:** 2x58w  
**SUPPLY VOLTAGE TYPE:** AC  
**NOMINAL VOLTAGE AC:** 230 V  
**VOLTAGE SUPPLY RANGE AC:** 220 V÷240 V  
**FREQUENCY SUPPLY RANGE:** 50 Hz÷60 Hz  
**POWER FACTOR (Cos fi):** 0.9  
**ABSORBED POWER:** 50 W  
**FLUX:** 7000 lm  
**EFFICIENCY:** 140 lm/W  
**Ta:** -20 °C÷40 °C  
**INSULATION CLASS:** II  
**CRI:** >80  
**CCT:** 4000 K  
**COLOR CONSISTENCY (SDCM):** SDCM2  
**LUMINOUS FLUX MAINTENANCE L70/B20:** 71000 h  
**LUMINOUS FLUX MAINTENANCE L70/B50:** 100000 h  
**LUMINOUS FLUX MAINTENANCE L80/B10:** 45000 h  
**LUMINOUS FLUX MAINTENANCE L80/B20:** 50000 h  
**LUMINOUS FLUX MAINTENANCE L80/B50:** 62000 h  
**LUMINOUS FLUX MAINTENANCE L90/B10:** 25000 h  
**LUMINOUS FLUX MAINTENANCE L90/B50:** 29500 h  
**BEAM ANGLE:** 140 °  
**DRIVER TYPE:** For constant current LED  
**CURRENT SUPPLY AC:** 215 mA

## MOUNTING AND APPLICATIONS

**MOUNTING:** Ceiling  
**ENVIRONMENT:** Indoor/Outdoor  
**APPLICATION:** Offices / Production / Warehouses

## MECHANICAL CHARACTERISTICS

**Dimension: Height:** 49 mm **Length:** 1500 mm **Width:** 68 mm  
**PRODUCT WEIGHT:** 0.58 kg  
**BODY MATERIAL: COLOUR** White RAL 9016  
**PROTECTION DEGREE:** IP65  
**MECHANICAL IMPACTS PROTECTION DEGREE:** IK06  
**QUANTITY PER BOX SINGLE/MULTIPLE/DELIVERY:** 1/12/

## CERTIFICATES AND STANDARDS

**STANDARDS:** UK SI 2021 No. 1095, EN 62471:2008, EN IEC 60598-1:2021, EN 60598-2-1:1989, EN IEC 63000:2018, EN 62493:2010, EN 61000-3-3:2013, REG. 2019/2020(EU), EN IEC 55015:2019 + A11:2020, EN IEC 61000-3-2 :2019, EN 60598-2-22:2014 + AC:2015 + AC:2016-05 + AC:2016-09 + A1:2020

