



MULTI-D

Square design housing made of sheet steel in universal versions.
Suitable for all variations of mounting. Single or double faced escape route marking by exchangeable pane.

Versions available for wall mounting (single faced), recessed / ceiling mounting, pendant and bracket mounting (double faced)

MOUNTING OPTIONS



MOUNTING OPTIONS WITH EQUIPMENT



TECHNICAL DATA

Housing: Sheet steel, grey (RAL 9006)
Aperture: Sheet steel, grey (RAL 9006)
Display pane: Methacrylate
Film: Methacrylate, printed

Service life $L_{80}B_{50}$: 50.000 h
Color stability: 3 SDCM



SELF-CONTAINED SUPPLY

Mains supply:
198 V–254 V/50 Hz

Specification:
Maintained or non-maintained mode

Ambient temperature:
Classic: 0 °C to +40 °C

Protection class:
I

DECENTRAL SUPPLY

Battery supply:
24 V +/- 20% DC

Mains supply:
24 V +/- 20% DC

Ambient temperature:
-20 °C to +40 °C

Protection class:
III







CENTRAL SUPPLY

Battery supply:
176 V–254 V







Mains supply:
198 V–254 V/50 Hz

Ambient temperature:
-20 °C to +40 °C




Protection class:
I







CLASSIC SELF-CONTAINED SUPPLY

Autotest Order code	Logica Order code	Logica FM Order code				 Autotest	 Logica	
Surface wall mounting (single faced indication), surface or recessed ceiling mounting, wire and rod suspension, bracket suspension (double faced indication) ¹								
36238	36239	36240	22 m	24	1 h / 3 h	NiMh 7.2V / 0.6 Ah	NiMh 7.2V / 1.2 Ah	7 VA
36241	36242	36243	34 m	32	1 h / 3 h	NiMh 7.2V / 0.6 Ah	NiMh 7.2V / 1.2 Ah	8 VA
36244	36245	36246	44 m	48	1 h / 3 h	NiMh 7.2V / 0.6 Ah	NiMh 7.2V / 1.2 Ah	10 VA

DECENTRAL SUPPLY

Sicuro24 Order code			
Surface wall mounting (single faced indication), surface or recessed ceiling mounting, wire and rod suspension, bracket suspension (double faced indication) ¹			
32098	22 m	24	2.2 W
32099	34 m	32	2.9 W
32100	44 m	48	4.3 W


CENTRAL SUPPLY

Sicuro230 Order code				
Surface wall mounting (single faced indication), surface or recessed ceiling mounting, wire and rod suspension, bracket suspension (double faced indication) ¹				
31151	22 m	24	5.8 VA / 2.5 W	
31152	34 m	32	7.4 VA / 3.5 W	
31153	44 m	48	9.4 VA / 4.7 W	

Please order mounting equipment separately

Order code	Description		
VD 22 m	VD 34 m	VD 44 m	
F95902	F95903	F95904	Recessed ceiling mounting set
F95905	F95905	F95905	Wire suspension, adjustable length 1.200 mm
F95901	F95901	F95901	Bracket suspension
F95906	F95906	F95906	Suspension rod, round, length 500 mm
F95914	F95915		Concrete ceiling box
F95917	F95918	F95191	Cable cover, white
F95920	F95921	F95922	Cable cover, V2A

Included in standard delivery

Order code	Description		
VD 22 m	VD 34 m	VD 44 m	
E16500M	E16501M	E16502M	Kit of exit sign films 
F95900	F95900	F95900	Adapter for wall mounting