



AESTETICA

Housing has a compact design with planar light-emitting surface and a clear insert. Lighting control is provided by a plastic reflector.

Versions for surface wall mounting and surface ceiling mounting or with additional equipment for recessed wall mounting and recessed ceiling mounting

MOUNTING OPTIONS



MOUNTING OPTIONS WITH EQUIPMENT



TECHNICAL DATA

Housing: Polycarbonate, white (RAL 9003)
Cover: Polycarbonate, clear
Reflector: Polycarbonate, white

Service life $L_{80}B_{20}$: 50.000 h
Color stability: 3 SDCM



SELF-CONTAINED SUPPLY


Mains supply: 198 V–254 V/50 Hz
Specification: Maintained or non-maintained mode
Ambient temperature: 0 °C to +40 °C
Protection class: II

DECENTRAL SUPPLY


Battery supply: 24 V +/- 20% DC
Mains supply: 24 V +/- 20% DC
Ambient temperature: -20 °C to +40 °C
Protection class: III

CENTRAL SUPPLY


Battery supply: 176 V–276 V
Mains supply: 198 V–254 V/50 Hz
Ambient temperature: -20 °C to +40 °C
Protection class: II




Polar diagram




Surface wall mounting



Recessed wall mounting







Surface ceiling mounting






Recessed ceiling mounting





CLASSIC SELF-CONTAINED SUPPLY

Order code			 Classic	
Surface and recessed wall/ceiling mounting, suspension for escape route lighting ¹				
16225	16	3 h	NiMh 3.6 V / 1.2 Ah	11 VA
16226	32	3 h	2 x NiMh 3.6 V / 1.2 Ah	11 VA

 DECENTRAL SUPPLY

Sicuro24 Order code			
Surface and recessed wall/ceiling mounting, suspension for escape route lighting ¹			
32069	20	120 lm	1.7 W

 CENTRAL SUPPLY

Sicuro230 Order code				
Surface and recessed wall/ceiling mounting, suspension for escape route lighting ¹				
31098	20	120 lm	4.8 VA / 1.8 W	

¹ For recessed wall and ceiling mounting please and suspension please order additional equipment separately

Please order additional equipment separately

Order code	Description
3733	Kit for recessed wall mounting
4266	Kit for recessed ceiling mounting
4265	Bracket suspension