




KUBUS

Housing made of flat sheet steel profiles with angular contours.
Additional light output in the case of wall mounting. Single or double-sided escape route signage is provided thanks to exchangeable inserts.

Versions for wall mounting or with equipment for ceiling mounting, wire or rod suspension mounting, mounting on brackets and chain/cable mounting

MOUNTING OPTIONS



MOUNTING OPTIONS WITH EQUIPMENT



TECHNICAL DATA

Housing: Sheet steel, white (RAL 9003)
Display pane: Methacrylate, clear

Service life $L_{80B_{50}}$: 50.000 h
Color stability: 3 SDCM



SELF-CONTAINED SUPPLY


Mains supply: 198 V–254 V/50 Hz
Specification: Maintained or non-maintained mode
Ambient temperature: LTO : -20 °C to 50 °C
Classic: 0 °C to +40 °C
Protection class: I

DECENTRAL SUPPLY


Battery supply: 24 V +/- 20% DC
Mains supply: 24 V +/- 20% DC
Ambient temperature: -20 °C to +40 °C
Protection class: III

CENTRAL SUPPLY


Battery supply: 176 V–276 V
Mains supply: 198 V–254 V/50 Hz
Ambient temperature: -20 °C to +40 °C
Protection class: I




Surface wall mounting




Surface ceiling mounting




Wire suspension



Suspension rod rectangular



Suspension rod round



Bracket suspension



SELF-CONTAINED SUPPLY

Autotest Order code	Logica Order code	Logica FM Order code					
------------------------	----------------------	-------------------------	--	--	--	--	--

Surface wall mounting (single faced indication)

37012	37013	37014	21 m	24	1 h / 3 h / 8 h	2 x LTO 7.2 V / 0.5 Ah	4.85 VA
37015	37016	37017	34 m	48	1 h / 3 h / 8 h	2 x LTO 7.2 V / 0.5 Ah	4.85 VA
37018	37019	37020	56 m	48	1 h / 3 h / 8 h	2 x LTO 7.2 V / 0.5 Ah	4.85 VA

Surface ceiling mounting, suspension, bracket suspension, chain or wire suspension (double faced indication)¹

37021	37022	37023	21 m	24	1 h / 3 h / 8 h	2 x LTO 7.2 V / 0.5 Ah	4.85 VA
37024	37025	37026	34 m	48	1 h / 3 h / 8 h	2 x LTO 7.2 V / 0.5 Ah	4.85 VA
37027	37028	37029	56 m	48	1 h / 3 h / 8 h	2 x LTO 7.2 V / 0.5 Ah	4.85 VA

CLASSIC SELF-CONTAINED SUPPLY

Autotest Order code	Logica Order code	Logica FM Order code						
------------------------	----------------------	-------------------------	--	--	--	--	--	--

Surface wall mounting (single faced indication)

36012	36013	36014	21 m	24	1 h / 3 h	NiMH 7.2V / 0.6 Ah	NiMH 7.2V / 1.2 Ah	7 VA
36015	36016	36017	34 m	48	1 h / 3 h	NiMH 7.2V / 0.6 Ah	NiMH 7.2V / 1.2 Ah	10 VA
36018	36019	36020	56 m	48	1 h / 3 h	NiMH 7.2V / 0.6 Ah	NiMH 7.2V / 1.2 Ah	10 VA

Surface ceiling mounting, Pendel, Bracket suspension (2-seitige Escape routekennzeichnung)¹

36021	36022	36023	21 m	24	1 h / 3 h	NiMH 7.2V / 0.6 Ah	NiMH 7.2V / 1.2 Ah	7 VA
36024	36025	36026	34 m	48	1 h / 3 h	NiMH 7.2V / 0.6 Ah	NiMH 7.2V / 0.6 Ah	10 VA
36027	36028	36029	56 m	48	1 h / 3 h	NiMH 7.2V / 0.6 Ah	NiMH 7.2V / 0.6 Ah	10 VA



DECENTRAL SUPPLY

Sicuro 24 Order code			
-------------------------	--	--	--

Surface wall mounting (single faced indication)

32004	21 m	24	2.5 W
32005	34 m	48	4.3 W
32006	56 m	48	4.3 W

Surface ceiling mounting, suspension, bracket suspension, chain or wire suspension (double faced indication)¹

32007	21 m	24	2.2 W
32008	34 m	48	4.3 W
32009	56 m	48	4.3 W



CENTRAL SUPPLY

Sicuro 230 Order code				
--------------------------	--	--	--	--

Surface wall mounting (single faced indication)

31004	21 m	24	5.8 VA / 2.5 W
31005	34 m	48	9.4 VA / 4.7 W
31006	56 m	48	9.4 VA / 4.7 W

Surface ceiling mounting, suspension, bracket suspension, chain or wire suspension (double faced indication)¹nung)¹

31007	21 m	24	5.8 VA / 2.5 W
31008	34 m	48	9.4 VA / 4.7 W
31009	56 m	48	9.4 VA / 4.7 W

¹ For surface ceiling mounting, wire and rod suspension, bracket suspension please order equipment separately

Please order exit sign equipment separately

Order code	Order code	Order code	Description	
VD 21 m	VD 34 m	VD 56 m		
E16604M	E16608M	E16134M	Exit sign pane	
E16605M	E16609M	E16135M	Exit sign pane	
E16606M	E16610M	E16136M	Exit sign pane	
E16616M	E16617M	E16618M	Exit sign pane	
E16620M	E16640M	E16645M	Exit sign pane	
E16622M	E16642M	E16647M	Exit sign pane	
E16621M	E16641M	E16646M	Exit sign pane	
E16623M	E16643M	E16648M	Exit sign pane	
E16607	E16611	E16234	Opal plastic pane, grey	
E16242	E16241	E16251	Opal plastic pane, white	

Please order additional equipment separately

Order code	Order code	Order code	Description
VD 21 m	VD 34 m	VD 56 m	
F95057	F95057	F95057	Adapter for ceiling mounting
F95600	F95600	F95600	Suspension rod, rectangular, 250 mm
F95601	F95601	F95601	Suspension rod, rectangular, 500 mm
F95602	F95602	F95602	Suspension rod, rectangular, 1.000 mm
F95400	F95400	F95400	Suspension rod, round, 500 mm
F95401	F95401	F95401	Wire suspension, max. 1.200 mm
F95055	F95056	F95070	Bracket suspension
F95067	F95067	F95067	Adapter for chain or wire suspension
F95032K	F95032K		Wire guard