




## KUBUS65

**High protection.** Housing made of sheet steel or sheet stainless steel with frame cover and a clear insert. Lighting control is provided by a specular aluminium reflector. Single or double-sided escape route signage is provided thanks to self-adhesive films.

Versions for wall mounting or with equipment for ceiling mounting or wire or rod suspension mounting, or mounting on brackets

### MOUNTING OPTIONS



### MOUNTING OPTIONS WITH EQUIPMENT



## TECHNICAL DATA

**Housing:** Sheet steel, white (RAL 9003)  
Stainless steel, V2A

**Display pane:** Methacrylate, clear

**Service life  $L_{80 B_{50}}$ :** 50.000 h

**Color stability:** 3 SDCM



### SELF-CONTAINED SUPPLY

**Mains supply:** 198 V–254 V/50 Hz

**Ambient temperature:** LTO: -20 °C to +50 °C  
Classic: 0 °C to +40 °C

**Specification:** Maintained or non-maintained mode

**Protection class:** I

### DECENTRAL SUPPLY

**Battery supply:** 24 V +/- 20% DC

**Ambient temperature:** -20 °C to +40 °C

**Mains supply:** 24 V +/- 20% DC

**Protection class:** III


### CENTRAL SUPPLY

**Battery supply:** 176 V–276 V


**Ambient temperature:** -20 °C to +40 °C

**Mains supply:** 198 V–254 V/50 Hz


**Protection class:** I




Surface wall mounting




Surface ceiling mounting



Suspension rod rectangular








Suspension rod round









Bracket suspension






## SELF-CONTAINED SUPPLY

Autotest Order code	Logica Order code	Logica FM Order code					
Surface wall mounting (single faced indication)							
<b>37060</b>	<b>37061</b>	<b>37062</b>	32 m	48	1 h / 3 h / 8 h	2 x LTO 7.2 V / 0.5 Ah	4.85 VA
Surface ceiling mounting, suspension, bracket suspension (double faced indication) <sup>1</sup>							
<b>37063</b>	<b>37064</b>	<b>37065</b>	32 m	48	1 h / 3 h / 8 h	2 x LTO 7.2 V / 0.5 Ah	4.85 VA
Stainless steel V2A surface wall mounting (single faced indication) <sup>1</sup>							
<b>37066</b>	<b>37067</b>	<b>37068</b>	32 m	48	1 h / 3 h / 8 h	2 x LTO 7.2 V / 0.5 Ah	4.85 VA
Surface ceiling mounting, suspension, bracket suspension (double faced indication) <sup>1</sup>							
<b>37069</b>	<b>37070</b>	<b>37071</b>	32 m	48	1 h / 3 h / 8 h	2 x LTO 7.2 V / 0.5 Ah	4.85 VA





## CLASSIC SELF-CONTAINED SUPPLY

Autotest Order code	Logica Order code	Logica FM Order code				 Autotest	 Logica	
Surface wall mounting (single faced indication)								
<b>36060</b>	<b>36061</b>	<b>36062</b>	32 m	48	1 h / 3 h	NiMH 7.2V / 06 Ah	NiMH 7.2V / 1.2 Ah	10 VA
Surface ceiling mounting, suspension, bracket suspension (double faced indication) <sup>1</sup>								
<b>36066</b>	<b>36067</b>	<b>36068</b>	32 m	48	1 h / 3 h	NiMH 7.2V / 06 Ah	NiMH 7.2V / 1.2 Ah	10 VA
Stainless steel V2A surface wall mounting (single faced indication) <sup>1</sup>								
<b>36072</b>	<b>36073</b>	<b>36074</b>	32 m	48	1 h / 3 h	NiMH 7.2V / 06 Ah	NiMH 7.2V / 1.2 Ah	10 VA
Surface ceiling mounting, suspension, bracket suspension (double faced indication) <sup>1</sup>								
<b>36078</b>	<b>36079</b>	<b>36080</b>	32 m	48	1 h / 3 h	NiMH 7.2V / 06 Ah	NiMH 7.2V / 1.2 Ah	10 VA


 DECENTRAL SUPPLY

Sicuro24 Order code			
Surface wall mounting (single faced indication)			
<b>32020</b>	32 m	48	4.3 W
Surface ceiling mounting, suspension, bracket suspension (double faced indication) <sup>1</sup>			
<b>32021</b>	32 m	48	4.3 W
Stainless steel V2A surface wall mounting (single faced indication) <sup>1</sup>			
<b>32022</b>	32 m	48	4.3 W
Surface ceiling mounting, suspension, bracket suspension (double faced indication) <sup>1</sup>			
<b>32023</b>	32 m	48	4.3 W


 CENTRAL SUPPLY

Sicuro230 Order code				
Surface wall mounting (single faced indication)				
<b>31020</b>	32 m	48	9.4 VA / 4.7 W	
Surface ceiling mounting, suspension, bracket suspension (double faced indication) <sup>1</sup>				
<b>31021</b>	32 m	48	9.4 VA / 4.7 W	
Stainless steel V2A surface wall mounting (single faced indication) <sup>1</sup>				
<b>31022</b>	32 m	48	9.4 VA / 4.7 W	
Surface ceiling mounting, suspension, bracket suspension (double faced indication) <sup>1</sup>				
<b>31023</b>	32 m	48	9.4 VA / 4.7 W	

<sup>1</sup> For surface wall mountin and all suspended versions, please order equipment separately

## Please order additional equipment separately

Order code	Description
White	V2A
<b>F95612</b>	<b>F95613</b> Adapter for ceiling mounting
<b>F95603</b>	<b>F95608</b> Suspension rod, rectangular, 100 mm
<b>F95604</b>	<b>F95609</b> Suspension rod, round, 500 mm
<b>F95605</b>	<b>F95610</b> Suspension rod, round, 1.000 mm
<b>F95606</b>	<b>F95611</b> Bracket suspension
<b>F95607</b>	<b>F95607</b> Wire guard

## Please order exit sign equipment separately

Order code	Description	
<b>E16700M</b>	Kit of exit sign films	
<b>E16701M</b>	Kit of exit sign films	