



MAXIMA


High protection. Body with clear convex shaped cover. Additional down-lighting provided by slots in the body. Single or double-sided escape route signage is provided thanks to exchangeable inserts.

Versions for wall mounting or with equipment for ceiling mounting, wire or rod suspension mounting, mounting on brackets and chain/cable mounting

MOUNTING OPTIONS



MOUNTING OPTIONS WITH EQUIPMENT



TECHNICAL DATA

Housing: Polycarbonate, grey (RAL 7035)
Polyester, grey (RAL 7035)

Display pane: Polycarbonate, clear

Service life $L_{80}B_{50}$: 50.000 h

Color stability: 3 SDCM



SELF-CONTAINED SUPPLY

Mains supply: 198 V–254 V/50 Hz

Specification: Maintained or non-maintained mode

Ambient temperature: LTO : -20 °C to 50 °C
Classic: 0 °C to +40 °C

Protection class: II

DECENTRAL SUPPLY

Battery supply: 24 V +/- 20% DC

Mains supply: 24 V +/- 20% DC

Ambient temperature: -20 °C to +40 °C

Protection class: III


CENTRAL SUPPLY

Battery supply: 176 V–276 V


Mains supply: 198 V–254 V/50 Hz

Ambient temperature: -20 °C to +40 °C


Protection class: II




Surface wall mounting




Surface ceiling mounting




Surface ceiling mounting + adapter



Suspension rod








Bracket suspension









Chain or wire suspension



SELF-CONTAINED SUPPLY




Autotest Order code	Logica Order code	Logica FM Order code					
Surface wall mounting (single faced indication)							
37054	37055	37056	32 m	2	1 h / 3 h / 8 h	2 x LTO 7.2 V / 0.5 Ah	4.85 VA
Surface ceiling mounting, suspension, bracket suspension, chain or wire (double faced indication) ¹							
37057	37058	37059	32 m	2	1 h / 3 h / 8 h	2 x LTO 7.2 V / 0.5 Ah	4.85 VA

CLASSIC SELF-CONTAINED SUPPLY

Autotest Order code	Logica Order code	Logica FM Order code						
Surface wall mounting (single faced indication)								
36054	36055	36056	32 m	2	1 h / 3 h	NiMh 7.2V / 0.6 Ah	NiMh 7.2V / 1.2 Ah	8 VA
Surface ceiling mounting, suspension, bracket suspension, chain or wire (double faced indication) ¹								
36057	36058	36059	32 m	2	1 h / 3 h	NiMh 7.2V / 0.6 Ah	NiMh 7.2V / 1.2 Ah	8 VA







DECENTRAL SUPPLY

Sicuro24 Order code			
Surface wall mounting (single faced indication)			
32018	32 m	2	2.9 W
Surface ceiling mounting, suspension, bracket suspension, chain or wire (double faced indication) ¹			
32019	32 m	2	2.9 W






CENTRAL SUPPLY

Sicuro230 Order code				
Surface wall mounting (single faced indication)				
31018	32 m	2	7.4 VA / 3.5 W	
Surface ceiling mounting, suspension, bracket suspension, chain or wire (double faced indication) ¹				
31019	32 m	2	7.4 VA / 3.5 W	

¹ For suspension and chain or wire suspension, please order equipment separately

Please order exit sign equipment separately

Order code	Description	
29002	Kit of exit sign film	
16917M	Kit of exit sign film	

Please order additional equipment separately

Order code	Description
F95700	Adapter for ceiling mounting and visible conduits
F95510	Suspension rod, round, 500 mm
F95511	Suspension rod, round, 1.000 mm
F95512	Suspension rod, round, 1.500 mm
3723	Adapter for chain or wire suspension
F95032K	Wire guard

Included in standard delivery

Order code	Description	
29001	Kit of exit sign film	