


## PIANA LED

Exit sign luminaire with square design, frame-display and light-guide-panel. Single or double-sided escape route signage is provided thanks to exchangeable display inserts.

Version for surface wall and ceiling mounting, recessed ceiling mounting and wire suspension



### MOUNTING OPTIONS



### TECHNICAL DATA

Housing:	ABS (RAL 9003)
Frame:	ABS (RAL 9003)
Film:	PMMA, printed



### SELF-CONTAINED SUPPLY


<b>Mains supply:</b> 198 V–254 V/50 Hz	<b>Ambient temperature:</b> LTO : -20 °C to +50 °C Classic: 0 °C to +40 °C
<b>Specification:</b> Maintained or non-maintained mode	<b>Protection class:</b> II

### DECENTRAL SUPPLY


<b>Battery supply:</b> 24 V +/- 20% DC	<b>Ambient temperature:</b> -20 °C to +40 °C
<b>Mains supply:</b> 24 V +/- 20% DC	<b>Protection class:</b> III

### CENTRAL SUPPLY


<b>Battery supply:</b> 176 V–276 V	<b>Ambient temperature:</b> -20 °C to +40 °C
<b>Mains supply:</b> 198 V–254 V/50 Hz	<b>Protection class:</b> II



Surface wall mounting




Surface ceiling mounting



Ceiling cutout:  
Viewing distance 24 m: 304 x 55 mm  
Viewing distance 30 m: 370 x 55 mm

Recessed ceiling mounting



Wire suspension



## SELF-CONTAINED SUPPLY

Autotest Order code	Logica Order code	Logica FM Order code					
Surface wall and ceiling mounting							
37168	37169	37170	24 m	28	1 h / 3 h / 8 h	2 x LTO 7.2 V / 0.5 Ah	4.85 VA
37171	37172	37173	30 m	28	1 h / 3 h / 8 h	2 x LTO 7.2 V / 0.5 Ah	4.85 VA
Wire suspension							
37174	37175	37176	24 m	28	1 h / 3 h / 8 h	2 x LTO 7.2 V / 0.5 Ah	4.85 VA
37177	37178	37179	24 m	28	1 h / 3 h / 8 h	2 x LTO 7.2 V / 0.5 Ah	4.85 VA

## CLASSIC SELF-CONTAINED SUPPLY

Autotest Order code						
Surface wall and ceiling mounting						
N94100AT	24 m	14	1 h	NiCd 3.6 V / 0.6 Ah	6 W / 3.5 VA	
N94101AT	24 m	14	3 h	NiCd 3.6 V / 0.6 Ah	6 W / 3.5 VA	
N94110AT	30 m	14	1 h	NiCd 3.6 V / 0.6 Ah	6 W / 3.5 VA	
N94111AT	30 m	14	3 h	NiCd 3.6 V / 0.6 Ah	6 W / 3.5 VA	
Wire suspension						
N94102AT	24 m	14	1 h	NiCd 3.6 V / 0.9 Ah	6 W / 3.5 VA	
N94103AT	24 m	14	3 h	NiCd 3.6 V / 0.9 Ah	6 W / 3.5 VA	
N94112AT	30 m	14	1 h	NiCd 3.6 V / 0.9 Ah	6 W / 3.5 VA	
N94113AT	30 m	14	3 h	NiCd 3.6 V / 0.9 Ah	6 W / 3.5 VA	

## SICURO<sup>LED</sup> DECENTRAL SUPPLY

Sicuro24 Order code			
Surface wall and ceiling mounting			
32085	24 m	28	2.9 W
32086	30 m	28	2.9 W
Wire suspension			
32087	24 m	28	2.9 W
32088	30 m	28	2.9 W

## SICURO<sup>LED</sup> CENTRAL SUPPLY

Sicuro230 Order code				
Surface wall and ceiling mounting				
31116	24 m	28	7.4 VA / 3.5 W	
31117	30 m	28	7.4 VA / 3.5 W	
Wire suspension				
31118	24 m	28	7.4 VA / 3.5 W	
31119	30 m	28	7.4 VA / 3.5 W	

### Please order mounting equipment separately

Order code	Description
VD 24m	VD 30m
F94001	Housing für recessed mounting
F94002	Housing für recessed mounting

### Please order exit sign equipment separately

Order code	Description	
VD 24m	VD 30m	
E16030M	Set of exit sign films	
E16029M	Set of exit sign films	
E16031M	Exit sign film	
E16032M	Exit sign film	