



ACCIAIO HIGH

High protection with high impact strength. Housing made of steel with die-cast aluminium caps. High-power LED with lighting control through special lenses for asymmetrically-emitted light distribution at extremely high luminaire intervals of > 100 m at heights of 2.5 to 20 m, e.g. in tunnels or hangars (illumination of paths with 1 lx).

Extremely resistant to both mechanical and chemical stress with wall bracket, swiveling

Version for wall mounting or ceiling mounting

MOUNTING OPTIONS



TECHNICAL DATA

Housing: Sheet steel, grey (RAL 7035)
Caps: Aluminium, grey (RAL 7035)
Lens: Methacrylate

Service life $L_{80/B_{20}}$: 50.000 h
Color stability: 3 SDCM



DECENTRAL SUPPLY

Battery supply:
24 V +/- 20% DC

Mains supply:
24 V +/- 20% DC

Ambient temperature:
-20 °C to +40 °C

Protection class:
I / III


CENTRAL SUPPLY

Battery supply:
176 V-276 V


Mains supply:
198V-254V/50Hz

Ambient temperature:
-20 °C to +40 °C


Protection class:
I



Polar diagram



Surface wall mounting



Surface ceiling mounting

SICURO LED DECENTRAL SUPPLY

Sicuro24 Order code	LED	Φ	P=
Surface wall and ceiling mounting, chain/wire suspension for escape route lighting			
32084	6	750 lm 1.500 lm	8 W / 16 W ¹

¹ Programmable via decentral supply

SICURO LED CENTRAL SUPPLY

Sicuro230 Order code	LED	Φ	S~	P=
Surface wall and ceiling mounting, chain/wire suspension for escape route lighting				
31114	6	2.250 lm	26 VA / 23.5 W	
Surface wall and ceiling mounting, chain/wire suspension for escape route lighting, EVG				
31115	6	2.250 lm	25.5 VA / 22 W	

Included in standard delivery

Order code	Description
15015	Wall bracket, swiveling (+/- 90°) ¹

¹ 1 wall bracket per luminaire necessary