



AESTETICA

Housing in compact design with plane light outlet area and clear cover. Light guidance through plastic reflector. 1-sided escape route indication through exchangeable escape sign foils, 2-sided escape route indication through exchangeable display panes.

Versions for surface wall and ceiling mounting or with additional accessories for recessed wall mounting, recessed ceiling mounting and bracket

MOUNTING TYPES



MOUNTING TYPES WITH ACCESSORIES



TECHNICAL DATA

Housing: Polycarbonate, white (RAL 9003)
Cover: Polycarbonate, transparent
Display pane / pane: PMMA, printed
Reflector: Polycarbonate, white

Service life $L_{80B_{20}}$: 50.000 h
Color stability: 3 SDCM
Color temperature: 5.700 K
Color rendering index: 80




DECENTRAL SUPPLY


Mains supply: 24 V +/- 20 % DC
Battery supply: 24 V +/- 20 % DC
Ambient temperature: -20 °C to +40 °C
Protection class: III

CENTRAL SUPPLY


Mains supply: 198 V – 254 V / 50 Hz
Battery supply: 176 V – 276 V
Ambient temperature: -20 °C to +40 °C
Protection class: II
Mains supply (alt.): 90 V – 254 V / 50/60 Hz
Battery supply (alt.): 90 V – 276 V




Surface wall and ceiling mounting




Surface ceiling mounting, display pane




Recessed wall and ceiling mounting, hollow




Recessed ceiling mounting, hollow, display pane



Recessed wall and ceiling mounting, massive



Recessed ceiling mounting, massive, display pane



Bracket, display pane

SICURO^{LED} DECENTRAL SUPPLY

Sicuro24 Order code				
-------------------------------	--	--	--	--

Surface wall mounting (1-sided escape route indication / illumination),
surface ceiling mounting (2-sided escape route indication / illumination)¹

32069	15 m	20	120 lm	1.7 W
--------------	------	----	--------	-------


SICURO^{LED} CENTRAL SUPPLY

Sicuro230 Order code					
--------------------------------	--	--	--	--	--

Surface wall mounting (1-sided escape route indication / illumination),
surface ceiling mounting (2-sided escape route indication / illumination)¹

31098	15 m	20	120 lm	4.8 VA / 1.8 W
--------------	------	----	--------	----------------

¹ Please order additional required accessories for recessed wall and ceiling mounting and bracket separately.



Please order escape sign accessories separately		
Order code	Description	
VD 15 m	VD 20 m	
16235	Escape sign pane, wall	
16236	Escape sign pane, wall	
16237	Escape sign pane, wall	
16233	Escape sign display pane, ceiling, bracket	
16234	Escape sign display pane, ceiling, bracket	

Please order accessories separately	
Order code	Description
4265	Bracket
3733	Recessed mounting set for massive walls and massive ceilings (concrete-cast housing)
4266	Recessed mounting set for hollow walls and hollow ceilings