



ACCIAIO HIGH

High type of protection and high impact resistance. Housing made of sheet steel with caps made of diecast aluminium. High-power LEDs with light guidance through special lenses for asymmetrical shining light distribution with extreme large luminaire distances of > 100 m at heights of 2.5 to 20 m, f. i. in tunnels or halls (illumination of escape routes with 1 lx). Extremely resistant against mechanical and chemical stress.

Versions for surface wall and ceiling mounting and chain/wire, additional accessory: swivelable wall holder

MOUNTING TYPES



TECHNICAL DATA

Housing:	Sheet steel, grey (RAL 7035)	Color stability:	3 SDCM
Caps:	Diecast aluminium, grey (RAL 7035)	Color temperature:	5.700 K
Lenses:	PMMA, transparent	Color rendering index:	80
Service life $L_{80}B_{20}$:	50.000 h		



DECENTRAL SUPPLY

Mains supply:	24 V +/- 20 % DC
Battery supply:	24 V +/- 20 % DC
Ambient temperature:	-20 °C to +40 °C
Protection class:	III

CENTRAL SUPPLY

Mains supply:	198V – 254V/50Hz
Battery supply:	176 V – 276 V
Ambient temperature:	-20 °C to +40 °C
Protection class:	I

Variant



Sicuro24

Sicuro230






–

2.250 lm



SICURO^{LED} DECENTRAL SUPPLY

Sicuro24 Order code	LED 	Φ = 	P= 
Surface wall mounting, surface ceiling mounting, chain/wire			
32084 ¹	6	750 lm 1.500 lm	8 W 16 W





¹ With S24 inverter module G31446, only for non-maintained mode, light flux / power programmable over S24 station.

² With S230 module 17382 and LED driver.

³ With LED driver.

⁴ 1 piece per luminaire required.

SICURO^{LED} CENTRAL SUPPLY

Sicuro230 Order code	LED 	Φ = 	S~ 	P= 
Surface wall mounting, surface ceiling mounting, chain/wire with luminaire monitoring (EÜ)				
31114 ²	6	2.250 lm	26 VA / 23.5 W	
Surface wall mounting, surface ceiling mounting, chain/wire with circuit monitoring (SÜ)				
31115 ³	6	2.250 lm	25.5 VA / 22 W	



Please order accessories separately	
Order code	Description
15015 ⁴	Wall holder, swiveable (+/- 90°)

