



ACCIAIO


High protection class combined exit sign luminaire / safety luminaire with high impact strength. The housing is made of zinc-coated sheet steel, the caps are made of plastic and the insert is made of tempered glass. The caps and the insert are securely fastened to the housing. Lighting control is provided by a highly reflective aluminium reflector. Single or double-sided escape route signage is provided thanks to exchangeable display inserts. Explosion protection for zone 2 (II 3G Ex nA IIB T4) and zone 22 (II 3D Ex tD A22 T100). Extremely resistant to both mechanical and chemical stress.

Versions for wall mounting and ceiling mounting with swivelling mount or for chain/cable mounting

MOUNTING OPTIONS



MOUNTING OPTIONS WITH EQUIPMENT



TECHNICAL DATA

Housing: Sheet steel, galvanized, grey (RAL 9003)

Caps: Polycarbonate / polybutyleneterephthalate, grey (RAL 7040)

Display pane: Methacrylate

Film: Methacrylate, printed

Reflector: Aluminium, specular

Service life $L_{80B_{50}}$: 50.000 h

Color stability: 3 SDCM



SELF-CONTAINED SUPPLY

Mains supply:
198 V–254 V/50 Hz

Specification:
Maintained or
non-maintained mode

Ambient temperature:
LTO: -20 °C to +50 °C
Classic: 0 °C to +40 °C

Protection class:
I

DECENTRAL SUPPLY

Battery supply:
24 V +/- 20% DC

Mains supply:
24 V +/- 20% DC

Ambient temperature:
-20 °C to +40 °C

Protection class:
III



CENTRAL SUPPLY

Battery supply:
176V–276V

Mains supply:
198V–254V/50Hz






Ambient temperature:
-20 °C to +40 °C

Protection class:
I














SELF-CONTAINED SUPPLY

Autotest Order code	Logica Order code	Logica FM Order code					
Surface wall mounting (single faced indication / area lighting), surface ceiling mounting, chain or wire suspension (double faced indication / area lighting)							
37090	37091	37092	38 m	32	1 h / 3 h / 8 h	2 x LTO 7.2 V / 0.5 Ah	4.85 VA





CLASSIC SELF-CONTAINED SUPPLY

Autotest Order code	Logica Order code	Logica FM Order code				 Autotest	 Logica	
Surface wall mounting (single faced indication / area lighting), surface ceiling mounting, chain or wire suspension (double faced indication / area lighting)								
15030	15030	15031	38 m	32	1 h / 3 h	NiMH 7,2.V / 1.2 Ah	NiMH 7.2V / 1.2 Ah	10 VA



 DECENTRAL SUPPLY

Sicuro24 Order code			
Surface wall mounting (single faced indication / area lighting), surface ceiling mounting, chain or wire suspension (double faced indication / area lighting)			
32055	38 m	32	4.3 W


 CENTRAL SUPPLY

Sicuro230 Order code				
Surface wall mounting (single faced indication / area lighting), surface ceiling mounting, chain or wire suspension (double faced indication / area lighting)				
31054	38 m	32	9.4 VA / 4.7 W	

Please order exit sign equipment separately

Order code	Description	
19064	Kit of exit sign display pane	

Included in standard delivery

Order code	Description
20122	Swivel bracket