


# QUADER



Housing made of sheet steel in square shape with cuboid, opal cover. 1-, 2- or 3-sided escape route indication through self-adhesive foils.

Versions for surface ceiling mounting and with additional accessories for pendulum and chain/wire

## MOUNTING TYPES



## MOUNTING TYPES WITH ACCESSORIES



## TECHNICAL DATA

**Housing:** Sheet steel, white (RAL 9003)  
**Cover:** PMMA, opal  
**Foil:** PVC, printed  
**Service life  $L_{80B_{20}}$ :** 50.000 h

**Color stability:** 3 SDCM  
**Color temperature:** 4.000 K  
**Color rendering index:** 80



## SELF-CONTAINED SUPPLY





**Mains supply:** 198 V – 254 V/50 Hz  
**Switching:** Maintained and non-maintained  
**Ambient temperature:** LTO: -20 °C to +45 °C  
 Classic 0 °C to +40 °C  
**Protection class:** I

## DECENTRAL SUPPLY

**Mains supply:** 24 V +/- 20 % DC  
**Battery supply:** 24 V +/- 20 % DC  
**Ambient temperature:** -20 °C to +40 °C  
**Protection class:** III






## CENTRAL SUPPLY

**Mains supply:** 198 V – 254 V/50 Hz  
**Battery supply:** 176 V – 276 V  
**Ambient temperature:** -20 °C to +40 °C  
**Protection class:** I  
**Mains supply (alt.):** 90 V – 254 V / 50/60 Hz  
**Battery supply (alt.):** 90 V – 276 V














## SELF-CONTAINED SUPPLY

Autotest Order code	Logica Order code	Logica FM Order code					
Surface ceiling mounting (3-sided escape route indication) <sup>1</sup>							
37072	37073	37074	22 m / 44 m	2	1 h / 3 h / 8 h	2 x LTO 7.2 V / 0.5 Ah	4.85 VA





## CLASSIC SELF-CONTAINED SUPPLY

Autotest Order code	Logica Order code	Logica FM Order code						
Surface ceiling mounting (3-sided escape route indication) <sup>1</sup>								
36084	36085	36086	22 m / 44 m	2	1 h / 3 h	NiMH 7.2V / 0.6 Ah	NiMH 7.2V / 1.2 Ah	10 VA

## SICURO<sup>®</sup> DECENTRAL SUPPLY






Sicuro24 Order code			
Surface ceiling mounting (3-sided escape route indication) <sup>1</sup>			
32024	22 m / 44 m	2	4.3 W

## SICURO<sup>®</sup> CENTRAL SUPPLY

Sicuro230 Order code				
Surface ceiling mounting (3-sided escape route indication) <sup>1</sup>				
31024	22 m / 44 m	2	9.4 VA / 4.7 W	

<sup>1</sup> Please order additional required accessories for pendulum and chain/wire separately. The pendulum mounting adaptor is required for all types of pendulums.

### Please order escape sign accessories separately

Order code	Description	
VD 22 m	VD 44 m	
F15330M	F15325M	Escape sign foil 
F15331M	F15326M	Escape sign foil 
F15332M	F15327M	Escape sign foil 
F15329M	F15328M	Escape sign foil 

### Please order accessories separately

Order code	Description
F95210	Pendulum mounting adaptor
F95600	Tubular pendulum, angular, 250 mm
F95601	Tubular pendulum, angular, 500 mm
F95602	Tubular pendulum, angular, 1.000 mm
F95400	Tubular pendulum, round, 500 mm
F95406	Lug set for chain and wire mounting