




## PLEXI LED


**Flat design housing in sheet steel and frameless display with integrated light guide panel made of clear plastic.** Homogeneous light distribution ensures optimal illumination of the exit sign. Single or double sided escape route signage is provided thanks to exchangeable films.

Versions for surface wall mounting, surface ceiling mounting, recessed ceiling mounting, or wire suspension with cables and with equipment for mounting on brackets

### MOUNTING OPTIONS



### MOUNTING OPTIONS WITH EQUIPMENT



## TECHNICAL DATA

**Housing:** Stainless steel, white (RAL 9003)  
**Display pane:** Light guide panel  
**Film:** Methacrylate, printed

**Service life  $L_{50}B_{50}$ :** 50.000 h  
**Color stability:** 3 SDCM



### SELF-CONTAINED SUPPLY






**Mains supply:** 198 V–254 V/50 Hz  
**Specification:** Maintained or non-maintained mode  
**Ambient temperature:** LTO: -20 °C to +50 °C  
 Classic: 0 °C to +40 °C  
**Protection class:** I

### DECENTRAL SUPPLY

**Battery supply:** 24 V +/- 20% DC  
**Mains supply:** 24 V +/- 20% DC  
**Ambient temperature:** -20 °C to +40 °C  
**Protection class:** III

### CENTRAL SUPPLY

**Battery supply:** 176 V–276 V  
**Mains supply:** 198 V–254 V/50 Hz  
**Ambient temperature:** -20 °C to +40 °C  
**Protection class:** I





## SELF-CONTAINED SUPPLY

Autotest Order code	Logica Order code	Logica FM Order code					
Surface wall mounting (single faced indication)							
37150	37151	37152	20 m	32	1 h / 3 h / 8 h	2 x LTO 7.2 V / 0.5 Ah	4.85 VA
37153	37154	37155	30 m	48	1 h / 3 h / 8 h	2 x LTO 7.2 V / 0.5 Ah	4.85 VA
Surface ceiling mounting, bracket suspension (double faced indication) <sup>1</sup>							
37144	37145	37146	20 m	32	1 h / 3 h / 8 h	2 x LTO 7.2 V / 0.5 Ah	4.85 VA
37147	37148	37149	30 m	48	1 h / 3 h / 8 h	2 x LTO 7.2 V / 0.5 Ah	4.85 VA
Recessed ceiling mounting (double faced indication)							
37138	37139	37140	20 m	32	1 h / 3 h / 8 h	2 x LTO 7.2 V / 0.5 Ah	4.85 VA
37141	37142	37143	30 m	48	1 h / 3 h / 8 h	2 x LTO 7.2 V / 0.5 Ah	4.85 VA
Wire suspension (double faced indication)							
37132	37133	37134	20 m	32	1 h / 3 h / 8 h	2 x LTO 7.2 V / 0.5 Ah	4.85 VA
37135	37136	37137	30 m	48	1 h / 3 h / 8 h	2 x LTO 7.2 V / 0.5 Ah	4.85 VA

## CLASSIC SELF-CONTAINED SUPPLY

Autotest Order code	Logica Order code	Logica FM Order code					Autotest		Logica	
Surface wall mounting (single faced indication)										
36194	36195	36196	20 m	32	1 h / 3 h	NiMh 7.2V / 1.2 Ah		NiMh 7.2V / 1.2 Ah		8 VA
36197	36198	36199	30 m	48	1 h / 3 h	NiMh 7.2V / 1.2 Ah		NiMh 7.2V / 1.2 Ah		10 VA
Surface ceiling mounting, bracket suspension (double faced indication) <sup>1</sup>										
36188	36189	36190	20 m	32	1 h / 3 h	NiMh 7.2V / 1.2 Ah		NiMh 7.2V / 1.2 Ah		8 VA
36191	36192	36193	30 m	48	1 h / 3 h	NiMh 7.2V / 1.2 Ah		NiMh 7.2V / 1.2 Ah		10 VA
Recessed ceiling mounting (double faced indication)										
36182	36183	36184	20 m	32	1 h / 3 h	NiMh 7.2V / 1.2 Ah		NiMh 7.2V / 1.2 Ah		8 VA
36185	36186	36187	30 m	48	1 h / 3 h	NiMh 7.2V / 1.2 Ah		NiMh 7.2V / 1.2 Ah		10 VA
Wire suspension (double faced indication)										
36176	36177	36178	20 m	32	1 h / 3 h	NiMh 7.2V / 1.2 Ah		NiMh 7.2V / 1.2 Ah		8 VA
36179	36180	36181	30 m	48	1 h / 3 h	NiMh 7.2V / 1.2 Ah		NiMh 7.2V / 1.2 Ah		10 VA

## SICURO<sup>LED</sup> DECENTRAL SUPPLY

Sicuro24 Order code			
Surface wall mounting (single faced indication)			
32081	20 m	32	2.9 W
32082	30 m	48	4.3 W
Surface ceiling mounting, bracket suspension (double faced indication) <sup>1</sup>			
32079	20 m	32	2.9 W
32080	30 m	48	4.3 W
Recessed ceiling mounting (double faced indication)			
32077	20 m	32	2.9 W
32078	30 m	48	4.3 W
Wire suspension (double faced indication)			
32075	20 m	32	2.9 W
32076	30 m	48	4.3 W

<sup>1</sup> For bracket suspension, please order equipment separately

## SICURO<sup>LED</sup> CENTRAL SUPPLY

Sicuro230 Order code				
Surface wall mounting (single faced indication)				
31110	20 m	32	7.4 VA / 3.5 W	
31111	30 m	48	9.4 VA / 4.7 W	
Surface ceiling mounting, bracket suspension (double faced indication) <sup>1</sup>				
31108	20 m	32	7.4 VA / 3.5 W	
31109	30 m	48	9.4 VA / 4.7 W	
Recessed ceiling mounting (double faced indication)				
31106	20 m	32	7.4 VA / 3.5 W	
31107	30 m	48	9.4 VA / 4.7 W	
Wire suspension (double faced indication)				
31104	20 m	32	7.4 VA / 3.5 W	
31105	30 m	48	9.4 VA / 4.7 W	

Please order exit sign equipment separately			
Order code	Description		
VD 20 m	VD 30 m		
16772	16781	Exit sign film	
16773	16782	Exit sign film	
16774	16783	Exit sign film	
16775	16784	Exit sign film	
16776	16785	Exit sign film	
16777	16786	Exit sign film	
16778	16787	Exit sign film	
16779	Kit of exit sign films single faced indication		
16780	Kit of exit sign films double faced indication		

Included in standard delivery		
Order code	Description	
VD 20 m		
16770	Kit of exit sign films single faced indication	
16771	Kit of exit sign films double faced indication	
Please order additional equipment separately		
Order code	Description	
VD 20m	VD 30 m	
F95944	F95944	Bracket suspension
F95962	F95963	Concrete ceiling box
F95964	F95965	Recessed ceiling mounting set