



DISPOS EVO

Square design housing made of sheet steel or stainless sheet steel in universal versions. Single or double-sided escape route signage is provided thanks to exchangeable display inserts.

Versions for surface wall mounting or surface ceiling mounting, or with equipment for recessed wall mounting, wire or rod suspension, or mounting on brackets

MOUNTING OPTIONS



MOUNTING OPTIONS WITH EQUIPMENT



TECHNICAL DATA

Housing:	Sheet steel, white (RAL 9003) Stainless steel (V2A)
Aperture:	Sheet steel, white (RAL 9003) Stainless steel (V2A)
Display pane:	Methacrylate, printed

Service life $L_{80} B_{50}$:	50.000 h
Color stability:	3 SDCM



SELF-CONTAINED SUPPLY







Mains supply: 198 V–254 V/50 Hz	Ambient temperature: LTO: -20 °C to +50 °C Classic: 0 °C to +40 °C
Specification: Maintained or non-maintained mode	Protection class: I

DECENTRAL SUPPLY

Battery supply: 24 V +/- 20% DC	Ambient temperature: -20 °C to +40 °C
Mains supply: 24 V +/- 20% DC	Protection class: III

CENTRAL SUPPLY

Battery supply: 176 V–276 V	Ambient temperature: -20 °C to +40 °C
Mains supply: 198 V–254 V/50 Hz	Protection class: I





SELF-CONTAINED SUPPLY

Autotest Order code	Logica Order code	Logica FM Order code					
------------------------	----------------------	-------------------------	--	--	--	--	--

Surface wall mounting (single faced indication), surface or recessed ceiling mounting, wire and rod suspension, bracket suspension (double faced indication)¹

37000	37001	37002	22 m	24	1 h / 3 h / 8 h	2 x LTO 7.2 V / 0.5 Ah	4.85 VA
37006	37007	37008	30 m	48	1 h / 3 h / 8 h	2 x LTO 7.2 V / 0.5 Ah	4.85 VA

Stainless steel V2A

Surface wall mounting (single faced indication), surface or recessed ceiling mounting, wire and rod suspension, bracket suspension (double faced indication)¹

37003	37004	37005	22 m	24	1 h / 3 h / 8 h	2 x LTO 7.2 V / 0.5 Ah	4.85 VA
37009	37010	37011	30 m	48	1 h / 3 h / 8 h	2 x LTO 7.2 V / 0.5 Ah	4.85 VA

CLASSIC SELF-CONTAINED SUPPLY

Autotest Order code	Logica Order code	Logica FM Order code						
------------------------	----------------------	-------------------------	--	--	--	--	--	--

Surface wall mounting (single faced indication), surface or recessed ceiling mounting, wire and rod suspension, bracket suspension (double faced indication)¹

36000	36001	36002	22 m	24	1 h / 3 h	NiMh 7.2V / 0.6 Ah	NiMh 7.2V / 1.2 Ah	7 VA
36006	36007	36008	30 m	48	1 h / 3 h	NiMh 7.2V / 0.6 Ah	NiMh 7.2V / 1.2 Ah	10 VA

Stainless steel V2A

Surface wall mounting (single faced indication), surface or recessed ceiling mounting, wire and rod suspension, bracket suspension (double faced indication)¹

36003	36004	36005	22 m	24	1 h / 3 h	NiMh 7.2V / 0.6 Ah	NiMh 7.2V / 1.2 Ah	7 VA
36009	36010	36011	30 m	48	1 h / 3 h	NiMh 7.2V / 0.6 Ah	NiMh 7.2V / 1.2 Ah	10 VA

SICURO^{LED} DECENTRAL SUPPLY

Sicuro24 Order code			
------------------------	--	--	--

Surface wall mounting (single faced indication), surface or recessed ceiling mounting, wire and rod suspension, bracket suspension (double faced indication)¹

32000	22 m	24	2.2 W
32002	30 m	48	4.3 W

Stainless steel V2A

Surface wall mounting (single faced indication), surface or recessed ceiling mounting, wire and rod suspension, bracket suspension (double faced indication)¹

32001	22 m	24	2.2 W
32003	30 m	48	4.3 W

SICURO^{LED} CENTRAL SUPPLY

Sicuro230 Order code				
-------------------------	--	--	--	--

Surface wall mounting (single faced indication), surface or recessed ceiling mounting, wire and rod suspension, bracket suspension (double faced indication)¹

31000	22 m	24	5.8 VA / 2.5 W
31002	30 m	48	9.4 VA / 4.7 W

Stainless steel V2A

Surface wall mounting (single faced indication), surface or recessed ceiling mounting, wire and rod suspension, bracket suspension (double faced indication)¹

31001	22 m	24	5.8 VA / 2.5 W
31003	30 m	48	9.4 VA / 4.7 W

¹ For recessed ceiling mounting, wire and rod suspension, please order equipment separately

Please order exit sign equipment separately

Order code	Description	
VD 22 m	VD 30 m	
E16260M	E16128M	Exit sign pane
E16262M	E16130M	Exit sign pane
E16261M	E16129M	Exit sign pane
E16310M	E16318M	Exit sign pane (double faced)
E16311M	E16319M	Exit sign pane (double faced)
E16263M	E16132M	Exit sign pane
E16312M	E16320M	Exit sign pane
E16313M	E16321M	Exit sign pane
E16435	Safety sign fire extinguisher	
E16436	Safety sign extinguisher hose	
E16437	Safety sign fire detector	

Included in standard delivery

VD 22 m	VD 30 m	Description
F95951	F95951	Adapter for wall mounting, white
F95958	F95958	Adapter for wall mounting, V2A

Please order additional equipment separately

Order code	Description	VD 22 m	VD 30 m
F95947	F95948	Recessed ceiling mounting set, white	
F95954	F95955	Recessed ceiling mounting set, V2A	
F95946	F95946	Wire suspension, max. 1.200 mm, white	
F95953	F95953	Wire suspension, max. 1.200 mm, V2A	
F95949	F95950	Bracket suspension, white	
F95956	F95957	Bracket suspension, V2A	
F95945	F95945	Suspension rod, round, 500 mm, white	
F95952	F95952	Suspension rod, round, 500 mm, V2A	
F95959	F95960	Concrete ceiling box	