



## S-IN

**Safety luminaire for steps.** Housing made of aluminium with frame or shade cover, exchangeable. Recessed mounting housing for solid steps included in delivery.

Version for recessed step mounting

### MOUNTING OPTIONS



### TECHNICAL DATA

|                      |                                     |
|----------------------|-------------------------------------|
| <b>Mounting:</b>     | Recessed step mounting              |
| <b>Housing:</b>      | Aluminium, grey (RAL 7030)          |
| <b>Cover:</b>        | Die cast aluminium, grey (RAL 7030) |
| <b>Display pane:</b> | Glass, opal                         |

|  |          |
|--|----------|
| <b>Service life <math>L_{80B_{20}}</math>:</b> | 50.000 h |
| <b>Color stability:</b>                        | 3 SDCM   |



### DECENTRAL SUPPLY

**Battery supply:**  
24 V +/- 20% DC

**Mains supply:**  
24 V +/- 20% DC

**Ambient temperature:**  
-20 °C to +40 °C

**Protection class:**  
III


### CENTRAL SUPPLY

**Battery supply:**  
176 V-276 V


**Mains supply:**  
198V-254V/50Hz

**Ambient temperature:**  
-20 °C to +40 °C


**Protection class:**  
I



Polar diagram



Recessed step mounting (solid)



Step cutout: 278 x 92 mm

Recessed step mounting (hollow)

**SICURO** LED **DECENTRAL SUPPLY**

Sicuro24  
Order code



Recessed step mounting for escape route lighting

|              |   |       |       |
|--------------|---|-------|-------|
| <b>32031</b> | 3 | 29 lm | 4.3 W |
|--------------|---|-------|-------|

**SICURO** LED **CENTRAL SUPPLY**

Sicuro230  
Order code



Recessed step mounting for escape route lighting

|              |   |       |                |
|--------------|---|-------|----------------|
| <b>31031</b> | 3 | 29 lm | 8.9 VA / 4.5 W |
|--------------|---|-------|----------------|