


H400 LED TOP3

High Bay

The H400 LED TOP3 is a fixture of the latest generation able to combine the advantages of the LED light source with state-of-the-art optic systems, as regards both performance and flexibility of application. The LED sources used, with very high efficiency, allow mounting at heights of more than 12 metres. The diffuser has an wide and uniform area of emission, allowing very low luminosity and therefore reduced glare with high visual comfort. The excellent mechanical characteristics (IP66-IK09) allow installation even in heavy-duty industrial environments. The fixture is available with three different optic modes: concentrating, wide and elliptical beam.

Unlike traditional industrial high bay fixtures, the H400 LED TOP3 is characterized by very compact dimensions, especially the height, which make it the ideal solution for sheds where there are overhead cranes or other moving structures. The fixture is designed to resist magnetic disturbances typical of industrial environments (EN 61000-6-2). In the versions with dimming, to ensure maximum energy saving, self-adapting technology is used on the sensor integrated in the fixture, to automatically adjust the emission of light according to the reading of the natural light present on the work surface.

A LED INVERTER is also available which transforms the fixture into an emergency maintained fixture, to light a section of the LED source in the event of a black-out.



Power * W	• Dimensions (mm) •			Weight max kg
	L	B	H	
400	425	413	121	7.7



GENERAL CHARACTERISTICS

- Equivalent Power*** 400 W
- Power supply** 195–265 V_{AC} 50/60 Hz
176–250 V_{DC}
- Standard** EN 60598-1, EN 60598-2-1,
EN 60598-2-22 (fundamental
requirements), EN 62471
(Photobiological hazard)
- Protection grade** IP66 with ventilation valve, IK09
- Working temp.** -30 °C ÷ +60 °C****
- Mounting** ceiling, suspension, busbar trunking
- Housing** Die-cast aluminium RAL 7040 white
- Grid** miro 4 Silver
- Optic** Sheet metal with parabolic development
in anti-iridescent, mirror finished,
anodised aluminium, Wide,
Concentrating, Ellipsoidal
- Diffuser***** Prismatic toughened glass 4 mm thick
- Driver** SELV electronic SD (cos $\varphi \geq 0.97$)
Electronic with intelligent dimming
- MTFB Control gear**** 100 000 h
- Luminous flux
maintenance**** >100 000 h (1× 400 W) (L80B20)
- Colour deviation** 3 SDCM

* Equivalent power for comparison with metal halide fixtures

** At environmental reference temperature of 25 °C

*** Available on request polycarbonate optic diffuser

**** At highest working temperature thermal protection may reduce the output power.

Accessories

supplied

Order code	Description
–	ANTI-VANDAL SCREWS
418319000	CABLE GLAND M20 WITH VENTILATION VALVE

SPECIAL VARIANTS: COLOUR TEMPERATURE ON REQUEST
Contact the Beghelli sales network

Accessories

supplied

Order code	Description
15039	OPTICOM PHOTSENSOR


Building automation to be ordered separately

Order code	Description
20102	BUILDING AUTOMATION CENTRAL UNIT
20124	BUILDING AUTOMATION CENTRAL UNIT WIFI
20104	2 INPUT INTERFACE – RADIO TRANSMITTER
15022	BUILDING AUTOMATION RADIO MODULE
15024	DALI MODULE
15034	1-10V MODULE

Accessories

to be ordered separately

Order code	Description
12658	PROTECTIVE GRID
12659	ELECTRIFIED TRACK BRACKET
12663	HIGH BAY SUSPENSION CABLES
12664	CEILING BRACKET
99-0205	HIGH BAY SUSPENSION CHAINS (1 m)
99-0206	HIGH BAY SUSPENSION CHAINS (2 m)



ELECTRIFIED TRACK MOUNTING BRACKET



12659 *to be ordered separately*

CEILING MOUNTING BRACKET



12664 *to be ordered separately*

SUSPENDED MOUNTING



12663 *to be ordered separately*
99-0205 *to be ordered separately*
99-0206 *to be ordered separately*

EMERGENCY WITH LED INVERTER

- TR
- AT
- LG
- LGFM


- 19377** INVERTER PLUG&LIGHT LED SE/SA 1H 20-60V IP65 *to be ordered separately*
- 19368** INVERTER PLUG&LIGHT LED SE/SA 1H 20-60V IP65 *to be ordered separately*
- 19355*** INVERTER LED AT/LG 6W 55V 123H *to be ordered separately*
- 19372*** INVERTER LED AT/LG 8W 55V 123H *to be ordered separately*
- 19390*** INVERTER EXT AT/LG 15W 55V 0,75-1-2-3-8H LTO *to be ordered separately*
- 19391*** INVERTER EXT AT/LG 15W 55V 0,75-1-2-3-8H LiFe *to be ordered separately*

* IP65 cover (order code 19376) is needed for the installation LGFM Module 19375


Efficiency and dimming

The increase in luminous efficacy (lm/W) and the useful life of the device may vary significantly according to the degree to which it is dimmed. Assuming an average level of 50% of the luminous flux, the following results are obtained with the H400 LED TOP3:


- Dimming SD** **50 %**
- Device duration** **+40 %**
- Luminous efficiency** **+10 %**



Wide optic



Concentrating optic



Elliptical optic

H400 LED TOP3

SmartDriver **SD**

Power* W	Order code	Description	Optic	LED Power W	Colour Temp. K	Colour rendering	Power consumption max W	N°LEDs	Flux of LEDs lm (Tj=25°C)	Flux of fixture lm	lm/W	Energy Class	Packaging
400	H400SDTOP3	RIF LED 400 DIFF SD 4000K	WIDE	202	4 000	>80	219	512	38 500	33 000	150	A++	1
400	H400CSDTOP3	RIF LED 400 CONC SD 4000K	CONCENTRATING	202	4 000	>80	219	512	37 800	32 400	148	A++	1
400	H400ESDTP3	RIF LED 400 ELLIT SD 4000K	ELLIPTICAL	202	4 000	>80	219	512	37 800	32 400	148	A++	1