# 86-02, 86-03 atomic

## Recessed luminaires

- separate/coupling in lines



## Material:

т

- · body: anodized aluminium profile and steel endings
- color: gray
- louvre: highly polished parabolic (IP20)
- diffuser: frosted acrylic glass (IP40)

Degree of protection: IP20, IP40

Rated voltage: 230V/50Hz

Control gear: electronic ballast; the luminaires are offered also in emergency version Mounting:

L I'

86-02 - recessed separate mounting (endings are supplied with luminaire)

86-03 - recessed coupling in lines mounting (endings must be ordered separately)

Accessories: univerzal holders (provided with luminaire)

To be ordered separately:

99-0102 - ending (1 pc) for recessed version coupling in lines (for louvre IP20)

99-0124 - ending (1 pc) for recessed version coupling in lines (for diffuser IP40)

99-0125 - coupler for coupling in lines for diffuser IP40 (couplers for IP20 are supplied with luminaire)

Application: restaurants, shops, hotels, finance houses, corridors and stairways

|                   | Code          | Power | Lamp    | Cap | LxBxH (mm) |
|-------------------|---------------|-------|---------|-----|------------|
| Separate mounting | 86-023/114/C2 | 1x14W | T5 lamp | G5  | 600x77x56  |
|                   | 86-023/124/C2 | 1x24W | T5 lamp | G5  | 600x77x56  |
|                   | 86-023/121/C2 | 1x21W | T5 lamp | G5  | 900x77x56  |
|                   | 86-023/139/C2 | 1x39W | T5 lamp | G5  | 900x77x56  |
|                   | 86-023/128/C2 | 1x28W | T5 lamp | G5  | 1200x77x56 |
|                   | 86-023/154/C2 | 1x54W | T5 lamp | G5  | 1200x77x56 |
|                   | 86-023/135/C2 | 1x35W | T5 lamp | G5  | 1500x77x56 |
|                   | 86-023/180/C2 | 1x80W | T5 lamp | G5  | 1500x77x56 |

Code Cap L'xBxH (mm) Power Lamp 86-033/114/C2 1x14W T5 lamp G5 580x77x56 86-033/124/C2 1x24W T5 lamp G5 580x77x56 Coupling in lines 86-033/121/C 2 1x21W T5 lamp G5 880x77x56 86-033/139/C2 1x39W T5 lamp G5 880x77x56 86-033/128/C2 1x28W T5 lamp G5 1180x77x56 86-033/154/C2 1x54W T5 lamp G5 1180x77x56 86-033/135/C2 1x35W T5 lamp G5 1480x77x56 86-033/180/C2 1x80W T5 lamp G5 1480x77x56

B (highly polished parabolic louvre)

- M (frosted acrylic glass)



#### Available emergency power-packs: Separate mounting:

- 1h autonomy (TR1) for versions 28-54-35-80W
- 3h autonomy (TR3) for version 28W only
- (Ord. code for example: 86-023/135/CB+++TR1)

## Coupling in lines:

- 1h autonomy (TR1) for versions 35W & 80W only
- 3h autonomy (TR3) for version 28W only
- (Ord. code for example: 86-033/128/CM+++TR3)

AT, LG options are not available.

### Available emergency modules:

Luminaire version with LED EM-module (TRLED) is extended by 100mm and equipped with EM-module at one end of the luminaire. (Ord. code for example: 86-033/154/CB+++TRLED) Available options: