



# Eco LED Bandiera



Ceiling version



Recessed version

## Emergency luminaires

Universal, two-sided emergency lighting fitting



Description: available in LED SA (maintained) 3 hours version

Material: a steel sheet finished by powder technology varnishing

Color : White

Degree of protection: IP 20

Rated voltage: 230V/50Hz

Recharging time: 24 hours

Mounting: recessed or surfaced mounting on ceiling

Accessories: (must be ordered separately)

99-0051 - adhesive legend left/right (set of 1 pc left and 1 pc right)

99-0052 - adhesive legend down (set of 2 pcs down)

99-0053 - adhesive legend left/right; german standard (set of 1 pc left and 1 pc right)

99-0054 - adhesive legend down; german standard (set of 2 pcs down)

Plastic board is supplied with the luminaire.

Distance visibility is 30 m.

W	Code	Article	Duration	Battery	Hole cut out (mm)	LxBxH (mm)	Kg	Pack./pcs.	Version
LED 8x0,1W	58-009/801/N	Eco LED Bandiera	3h	NiMH 4.8V 0.75Ah	-	332x55x246	2,9	1	surfaced
LED 8x0,1W	58-029/801/N	Eco LED Bandiera	3h	NiMH 4.8V 0.75Ah	360x60	396x81x247	2,8	1	recessed