



KUBUS65

Housing made of flat sheet steel profiles with angular contours and a clear insert. Lighting control is provided by a aluminium reflector. Lighting control is provided by a highly reflective aluminium reflector. Version in stainless steel is just suitable for indoor solutions.

Version for surface ceiling mounting

MOUNTING OPTIONS



TECHNICAL DATA

Housing: Sheet steel, white (RAL 9003)
Stainless steel, V2A

Cover: Methacrylate, clear

Reflector: Aluminium, specular

Service life $L_{80B_{20}}$: 50.000 h

Color stability: 3 SDCM



SELF-CONTAINED SUPPLY

Mains supply: 198 V–254 V/50 Hz

Specification: Maintained or non-maintained mode

Ambient temperature: LTO: -20 °C to +50 °C
Classic: 0 °C to +40 °C

Protection class: I

DECENTRAL SUPPLY

Battery supply: 24V +/- 20% DC

Mains supply: 24V +/- 20% DC

Ambient temperature: -20 °C to +40 °C

Protection class: III


CENTRAL SUPPLY

Battery supply: 176 V–276 V


Mains supply: 198V–254V/50Hz

Ambient temperature: -20 °C to +40 °C

Protection class: I



Polar diagram



Surface ceiling mounting



SELF-CONTAINED SUPPLY

Autotest Order code	Logica Order code	Logica FM Order code	LED	Φ 1 h	Φ 3 h	Φ 8 h		
Surface ceiling mounting suitable for escape route lighting								
37060	37061	37062	48	336 lm	168 lm	46 lm	2 x LTO 7.2 V / 0.5 Ah	4.85 VA
Version in V2A								
37066	37067	37068	48	336 lm	168 lm	46 lm	2 x LTO 7.2 V / 0.5 Ah	4.85 VA

CLASSIC SELF-CONTAINED SUPPLY

Autotest Order code	Logica Order code	Logica FM Order code	LED	Φ 1 h	Φ 3 h	Autotest	Logica	
Surface ceiling mounting suitable for escape route lighting								
36060	36061	36062	48	336 lm	227 lm	NiMH 7.2V / 0.6 Ah	NiMH 7.2V / 1.2 Ah	10 VA
Version in V2A								
36072	36073	36074	48	336 lm	227 lm	NiMH 7.2V / 0.6 Ah	NiMH 7.2V / 1.2 Ah	10 VA

DECENTRAL SUPPLY

Sicuro24 Order code	LED	Φ	P=
Surface ceiling mounting suitable for escape route lighting			
32020	48	350 lm	4.3 W
Version in V2A			
32022	48	350 lm	4.3 W

CENTRAL SUPPLY

Sicuro230 Order code	LED	Φ	S~	P=
Surface ceiling mounting suitable for escape route lighting				
31020	48	350 lm	9.4 VA / 4.7 W	
Version in V2A				
31022	48	350 lm	9.4 VA / 4.7 W	

Please order additional equipment separately

Order code	Description
F95607	Wire guard