



## AESTETICA

Housing has a compact design with planar light-emitting surface and a clear insert. Lighting control is provided by a plastic reflector. Single-sided escape route signage is provided thanks to exchangeable display films, double sided escape route signage is provided by exchangeable display inserts.

Versions for surface wall mounting and surface ceiling mounting or with additional equipment for recessed wall mounting, recessed ceiling mounting and bracket suspension mounting

### MOUNTING OPTIONS



### MOUNTING OPTIONS WITH EQUIPMENT



## TECHNICAL DATA

**Housing:** Polycarbonate, white (RAL 9003)  
**Cover:** Polycarbonate, clear  
**Display pane:** Methacrylate, printed  
**Reflector:** Polycarbonate, white

**Service life  $L_{50}B_{50}$ :** 50.000 h  
**Color stability:** 3 SDCM



### SELF-CONTAINED SUPPLY






**Mains supply:** 198 V–254 V/50 Hz  
**Ambient temperature:** Classic: 0 °C to +40 °C  
**Specification:** Maintained or non-maintained mode  
**Protection class:** II

### DECENTRAL SUPPLY






**Battery supply:** 24 V +/- 20% DC  
**Ambient temperature:** -20 °C to +40 °C  
**Mains supply:** 24 V +/- 20% DC  
**Protection class:** III

### CENTRAL SUPPLY




**Battery supply:** 176 V–276 V  
**Ambient temperature:** -20 °C to +40 °C  
**Mains supply:** 198 V–254 V/50 Hz  
**Protection class:** II







## CLASSIC SELF-CONTAINED SUPPLY

<b>Order code</b>					Classic	
Surface or recessed wall mounting (single face indication), surface or wall recessed ceiling mounting (double faced indication), suspension and bracket suspension (double faced indication) <sup>1</sup>						
<b>16225</b>	15 / 20 m	16	3 h	NiMh 3.6 V / 1.2 Ah		11 VA
<b>16226</b>	15 / 20 m	32	3 h	2 x NiMh 3.6 V / 1.2 Ah		11 VA






## SICURO<sup>®</sup> DECENTRAL SUPPLY

<b>Sicuro24</b> <b>Order code</b>			
Surface or recessed wall mounting (single faced indication), surface or recessed ceiling mounting (double faced indication), suspension and bracket suspension (double faced indication) <sup>1</sup>			
<b>32069</b>	15 / 20 m	20	1.7 W

## SICURO<sup>®</sup> CENTRAL SUPPLY

<b>Sicuro230</b> <b>Order code</b>				
Surface or recessed wall mounting (single faced indication), surface or recessed ceiling mounting (double faced indication), suspension and bracket suspension (double faced indication) <sup>1</sup>				
<b>31098</b>	15 / 20 m	20	4.8 VA / 1.8 W	

<sup>1</sup> For recessed wall / ceiling mounting in cavity walls or hollow ceilings, please order required equipment separately

Please order exit sign equipment separately		
Order code	Description	
<b>VD 15 m</b>	<b>VD 20 m</b>	
<b>16235</b>	Exit sign film	
<b>16236</b>	Exit sign film	
<b>16237</b>	Exit sign film	
<b>16233</b>	Exit sign display pane	
<b>16234</b>	Exit sign display pane	

Please order additional equipment separately	
Order code	Description
<b>4265</b>	Bracket suspension
<b>3733</b>	Kit for recessed wall mounting
<b>4266</b>	Kit for recessed ceiling mounting