

Iron Flag



IRONFLAG IP65 AT 30M SE/SA

SYSTEM:AT

Beghelli Code: **19818**



Description: Emergency

EAN:

ELECTRICAL AND LIGHTING TECHNICAL CHARACTERISTIC

LAMPHOLDER: None

SUPPLY VOLTAGE TYPE: AC

NOMINAL VOLTAGE AC: 230 V

VOLTAGE SUPPLY RANGE AC: 207 V÷253 V

FREQUENCY SUPPLY RANGE: 50 Hz÷60 Hz

POWER FACTOR (Cos ϕ): 0.55

MAX ABSORBED POWER NM: 5 W

EMERGENCY DIAGNOSTIC TYPE: AT

DURATION: 1 / 1.5 / 2 / 3 / 8 h

BATTERY TYPE: LiFe

BATTERY: 2 x LiFe 6.4V 0.6Ah

REST MODE: optional

RECHARGING TIME: 12 h

DURATION TEST FREQUENCY: 182 day

FUNCTIONAL TEST FREQUENCY: 28 day

PICTOGRAM INCLUDED: y

VISIBILITY DISTANCE: 30 m

Ta: 0 °C÷40 °C

INSULATION CLASS: I

CRI: >80

CCT: 4000 K

PHOTOBIOLOGICAL RISK: RG0

MOUNTING AND APPLICATIONS

ENVIRONMENT: Indoor/Outdoor

APPLICATION: Offices / Public Areas / Shops / Safety Sign

MECHANICAL CHARACTERISTICS

Dimension: Height: 55 mm Length: 351 mm Width: 223 mm

PRODUCT WEIGHT: 0.7 kg

BODY MATERIAL: Aluminium extrusion **COLOUR** Aluminium

PROTECTION DEGREE: IP65

MECHANICAL IMPACTS PROTECTION DEGREE: IK05

GLOW WIRE: 850° - 30s.

QUANTITY PER BOX SINGLE/MULTIPLE/DELIVERY: 1/6/

CERTIFICATES AND STANDARDS

STANDARDS: CEI EN 60598-2-22, CEI EN 62034, 2009/125/CE, 874/2012/CE, 2014/30/EU, 2014/35/EU