

Power Light



POWER L 1000W 10° C70 5K 0-10V

Beghelli Code: **41014**



SYSTEM:0-10V



Description: Lighting
EAN: 8002219862839

ELECTRICAL AND LIGHTING TECHNICAL CHARACTERISTIC

SUPPLY VOLTAGE TYPE: AC/DC
NOMINAL VOLTAGE AC: 230 V
VOLTAGE SUPPLY RANGE AC: 100 V+240 V
FREQUENCY SUPPLY RANGE: 50 Hz+60 Hz
POWER FACTOR (Cos ϕ): 0.95
VOLTAGE SUPPLY RANGE DC: 142+431 VOLT
ABSORBED POWER: 1000 W
FLUX: 130000 lm
EFFICIENCY: 130 lm/W
Ta: -30 °C+50 °C
INSULATION CLASS: I
CRI: >70
CCT: 5000 K
COLOR CONSISTENCY (SDCM): SDCM3
LUMINOUS FLUX MAINTENANCE L80/B50: 80000 h
BEAM ANGLE: 10 °
LED NUMBER: 480
DRIVER TYPE: For constant current LED (Dimmable 1-10V)
DRIVER LIFE MTBF: 100000 h
DIMMER TYPE: 0-10V
INRUSH: 60 A,
PHOTOBIOLOGICAL RISK: RG0

MOUNTING AND APPLICATIONS

ENVIRONMENT: Outdoor

MECHANICAL CHARACTERISTICS

Dimension: Height: 138 mm **Length:** 966 mm **Width:** 510 mm
PRODUCT WEIGHT: 31.8 kg
BODY MATERIAL: Die-cast aluminium **COLOUR** Black
COVER / DIFFUSER MATERIAL: Tempered glass
LENSES MATERIAL: Transparent polycarbonate
WIND SURFACED EXPOSED: 4029 cm²
PROTECTION DEGREE: IP66
MECHANICAL IMPACTS PROTECTION DEGREE: IK09
GLOW WIRE: 850° - 30s.
QUANTITY PER BOX SINGLE/MULTIPLE/DELIVERY: 1//

CERTIFICATES AND STANDARDS

STANDARDS: CEI EN 60598-1, EN 62471, 2009/125/CE, 874/2012/CE, 2014/30/EU, 2014/35/EU, CEI EN 60598-2-5


Power Light



POWER L 1000W 10° C70 5K 0-10V

SYSTEM:0-10V

Beghelli Code: **41014**



Accessories to be order separately



40933

PUNTATORE LASER