

EXIT DF60M SA 1/2/3H RM LF

SYSTEM:TR

Beghelli Code: **4322**



Description: Emergency
EAN: 8002219726858

ELECTRICAL AND LIGHTING TECHNICAL CHARACTERISTIC

LAMPHOLDER: None
SUPPLY VOLTAGE TYPE: AC
NOMINAL VOLTAGE AC: 230 V
VOLTAGE SUPPLY RANGE AC: 207 V÷253 V
FREQUENCY SUPPLY RANGE: 50 Hz÷60 Hz
POWER FACTOR (Cos ϕ): 0.5
MAX ABSORBED POWER NM: 3 W
EMERGENCY DIAGNOSTIC TYPE: TR
DURATION: 1 / 2 / 3 h
BATTERY TYPE: LiFe
BATTERY: LiFe 3.2V 1.5Ah
REST MODE: y
RECHARGING TIME: 24 h
PICTOGRAM INCLUDED: y
VISIBILITY DISTANCE: 60 m
Ta: 0 °C÷40 °C
INSULATION CLASS: II
CRI: >80
LED NUMBER: 42
CURRENT SUPPLY AC: 26 mA

MOUNTING AND APPLICATIONS

ENVIRONMENT: Indoor
APPLICATION: Offices / Safety Sign / Public Areas / Shops

MECHANICAL CHARACTERISTICS

Dimension: Height: 30 mm **Length:** 629 mm **Width:** 355 mm
PRODUCT WEIGHT: 1 kg
BODY MATERIAL: Polycarbonate **COLOUR:** White RAL 9003
COVER / DIFFUSER MATERIAL: PMMA transparent thermoplastic
PROTECTION DEGREE: IP40
MECHANICAL IMPACTS PROTECTION DEGREE: IK05
GLOW WIRE: 850° - 30s.
QUANTITY PER BOX SINGLE/MULTIPLE/DELIVERY: 1/6/

CERTIFICATES AND STANDARDS


STANDARDS: CEI EN 62034, CEI EN 62471, 2004/108/CE, 2006/95/CE, CEI EN 60598-2-22

EXIT DF60M SA 1/2/3H RM LF

SYSTEM:TR

Beghelli Code: **4322**

Accessories to be order separately



14771
SOSPENSIONE MONO/BI
LAMPADA



19045
STAFFA A PARETE X
BANDIERA F65



4315
SOSPEN TIGES L250



4316
SOSPEN TIGES L500



4317
SOSPEN TIGES L1000



4319
KIT BINARIO TRIFASE UP LED



2730
INIBIT 973 COMANDO R.MODE

Spare parts



415436001
LI-FEPO4 3.2V 1.5AH 18650