

# Power Light



POWER L 750W 10° C70 4K 0-10V

Beghelli Code: **41005**



SYSTEM:0-10V



**Description:** Lighting  
**EAN:** 8002219862631

## ELECTRICAL AND LIGHTING TECHNICAL CHARACTERISTIC

**SUPPLY VOLTAGE TYPE:** AC/DC  
**NOMINAL VOLTAGE AC:** 230 V  
**VOLTAGE SUPPLY RANGE AC:** 100 V+240 V  
**FREQUENCY SUPPLY RANGE:** 50 Hz+60 Hz  
**POWER FACTOR (Cos fi):** 0.95  
**VOLTAGE SUPPLY RANGE DC:** 142+431 VOLT  
**ABSORBED POWER:** 750 W  
**FLUX:** 97500 lm  
**EFFICIENCY:** 130 lm/W  
**Ta:** -30 °C+50 °C  
**INSULATION CLASS:** I  
**CRI:** >70  
**CCT:** 4000 K  
**COLOR CONSISTENCY (SDCM):** SDCM3  
**LUMINOUS FLUX MAINTENANCE L80/B50:** 80000 h  
**BEAM ANGLE:** 10 °  
**LED NUMBER:** 360  
**DRIVER TYPE:** For constant current LED (Dimmable 1-10V)  
**DRIVER LIFE MTBF:** 100000 h  
**DIMMER TYPE:** 0-10V  
**INRUSH:** 60 A,  
**PHOTOBIOLOGICAL RISK:** RG0

## MOUNTING AND APPLICATIONS

**ENVIRONMENT:** Outdoor

## MECHANICAL CHARACTERISTICS

**Dimension: Height:** 138 mm **Length:** 654 mm **Width:** 510 mm  
**PRODUCT WEIGHT:** 25.2 kg  
**BODY MATERIAL:** Die-cast aluminium **COLOUR** Black  
**COVER / DIFFUSER MATERIAL:** Tempered glass  
**LENSES MATERIAL:** Transparent polycarbonate  
**WIND SURFACED EXPOSED:** 2992 cm<sup>2</sup>  
**PROTECTION DEGREE:** IP66  
**MECHANICAL IMPACTS PROTECTION DEGREE:** IK09  
**GLOW WIRE:** 850° - 30s.  
**QUANTITY PER BOX SINGLE/MULTIPLE/DELIVERY:** 1//

## CERTIFICATES AND STANDARDS

**STANDARDS:** CEI EN 60598-1, EN 62471, 2009/125/CE, 874/2012/CE, 2014/30/EU, 2014/35/EU, CEI EN 60598-2-5


# Power Light



POWER L 750W 10° C70 4K 0-10V

SYSTEM:0-10V

Beghelli Code: **41005**



## Accessories to be order separately



**40931**  
STAFFA CURVA 300/400W



**40932**  
TESTA PALO



**40933**  
PUNTATORE LASER