



HighBay HE

HIGHBAY HE 200W 32000lm 4K

High-efficiency industrial reflector suitable for high installation, with die-cast aluminium body and circular PMMA lens.

CE

Order code 76308

EAN 8002219906700

Technical specifications

Absorbed Power	200 W
Supply voltage type	AC
Nominal voltage (AC)	230 Vac
Ambient temperature (min)	-20 °C
Ambient temperature (max)	45 °C
Insulation class	I
CCT light tone	4000 K
LED number	297
Photobiological risk	RG0
Beam angle	90 °
Colour consistency	SDCM5
CRI color rendering	>80
Diameter	320 mm
Efficiency	160 lm/W
Frequency (max)	60 Hz
Frequency (min)	50 Hz
Power factor	0.95
Glow wire strength	650 °C - 30s.
HACCP	Yes
Inrush current	65 A
Inrush time	0.5
Luminaire flux	32000 lm
Luminous flux L70B10	71000 h
Luminous flux L70B50	100000 h
Luminous flux L80B10	45000 h
Luminous flux L80B20	50000 h
Luminous flux L80B50	62000 h
Luminous flux L90B10	25000 h
Luminous flux L90B50	29500 h
Mounting	Suspension
Voltage supply range (max)	240 V
Voltage supply range (min)	120 V

Installation and applications

Environment **Secondary Areas**

Mechanical specifications

Height	118 mm
Weight	2.35 Kg
Body material	Die-cast aluminium
Colour housing	Black RAL 9005




Cover material	PMMA transparent thermoplastic
Lens material	PMMA transparent thermoplastic
Protection grade IP	IP65
Protection grade IK	IK08


Certifications and norms

UK SI 2021 No. 1095, EN 62471:2008, EN IEC 60598-1:2021, EN 60598-2-1:1989, EN IEC 63000:2018, EN 62493:2010, EN 61000-3-3:2013, REG. 2019/2020(EU), EN IEC 55015:2019 + A11:2020, EN IEC 61000-3-2 :2019

Accessories



40915
MOTION SENSOR HIGHBAY
HE



40919
STAFFA HIGHBAY HE LED
200W