



BS UNO Modula

BS UNO MODULA DALI 60W 4K



Order code 41315

EAN 8002219894618



Technical specifications



Absorbed Power	60 W
Supply voltage type	AC/DC
Nominal voltage (AC)	230 Vac
Ambient temperature (min)	-20 °C
Ambient temperature (max)	40 °C
Insulation class	II
CCT light tone	4000 K
LED number	240
Out current (Qty max)	350
Photobiological risk	RG0
Colour consistency	SDCM3
Colour reflector	White
CRI color rendering	>80
Driver type	DALI
Ballast	For constant current LED (DALI)
Efficiency	167 lm/W
Frequency (max)	60 Hz
Frequency (min)	50 Hz
Glow wire strength	850 °C - 30s.
HACCP	Yes
Luminaire flux	10000 lm
Luminous flux L70B10	160000 h
Luminous flux L70B50	220000 h
Luminous flux L80B10	100000 h
Luminous flux L80B20	110000 h
Luminous flux L80B50	140000 h
Luminous flux L90B10	60000 h
Luminous flux L90B50	70000 h
Mounting	Ceiling
Nominal voltage (DC)	216 Vdc
Voltage supply range (DC)	176÷250 VOLT
Voltage supply range (max)	265 V
Voltage supply range (min)	93 V

Installation and applications

Environment	Secondary Areas
Application	Industrial Areas, Production, Warehouses

Mechanical specifications

Height	100 mm
Length	1200 mm
Width	118 mm



Weight	1.9 Kg
Body material	Polycarbonate
Colour housing	Grey RAL 7040
Cover material	Transparent polycarbonate
Diffuser finiture	Clear
Reflector material	White Lacquered Aluminium
Protection grade IP	IP65
Protection grade IK	IK09

Certifications and norms

-, EN 60598-2-22:2014 + AC:2015 +
AC:2016-05 + AC:2016-09 + A1:2020

Accessories



8063
BS100 GRIGLIA PROTEZ
36/58W



8063/1
GR STAFFA UNICA GRIGLIA
8063

Inverter accessories



15060
MODULO LG230



15059
MODULO LG24



15068
MODULO TR 6W 1/3H BS
UNO