



Downlight Ultra Compact LED

DWL LED 8W 4000K

Order code **71051**

EAN 8002219722706

Technical specifications

Absorbed Power	8 W
Supply voltage type	AC
Nominal voltage (AC)	230 Vac
Ambient temperature (min)	-20 °C
Ambient temperature (max)	40 °C
Insulation class	II
CCT light tone	4000 K
Beam angle	110 °
Colour consistency	SDCM3
CRI color rendering	>80
Diameter	85 mm
Ballast	For constant current LED
Efficiency	90 lm/W
Frequency (max)	60 Hz
Frequency (min)	50 Hz
Power factor	0.55
Glow wire strength	650 °C - 30s.
Luminaire flux	720 lm
Voltage supply range (max)	253 V
Voltage supply range (min)	207 V

Installation and applications

Environment	Offices
Application	Offices, Shops

Mechanical specifications

Height	30 mm
Weight	0.1 Kg
Colour housing	White
Cover material	ABS
Protection grade IP	IP40/IP42
Protection grade IK	IK05

Certifications and norms

UK SI 2021 No. 1095, EN IEC 55015:2019
+ A11:2020, EN IEC 61000-3-2 :2019, EN
61547:2009, EN 62471:2008, EN IEC
60598-1:2021, EN 60598-2-2:2012, EN
IEC 63000:2018, EN 62493:2010, EN
61000-3-3:2013

