



Full Moon Ring CCT

FULLMOON RING IP65 40WCCT SENS



Order code 75378

EAN 8002219906571

Technical specifications

Absorbed Power	40 W
Supply voltage type	AC
Nominal voltage (AC)	230 Vac
Ambient temperature (min)	-10 °C
Ambient temperature (max)	45 °C
Insulation class	II
CCT light tone	3000 K, 4000 K, 6500 K
CCT (max)	6500 K
CCT (min)	3000 K
Photobiological risk	RG0
CRI color rendering	>80
Diameter	400 mm
Efficiency	100 lm/W
Frequency (max)	60 Hz
Frequency (min)	50 Hz
Power factor	0.9
Movement sensor	Yes
Luminaire flux	4000 lm
Luminous flux L70B10	57000 h
Luminous flux L70B50	100000 h
Luminous flux L80B10	36000 h
Luminous flux L80B20	50000 h
Luminous flux L80B50	49600 h
Luminous flux L90B10	20000 h
Luminous flux L90B50	23600 h
Voltage supply range (max)	240 V
Voltage supply range (min)	220 V

Mechanical specifications

Height	55 mm
Length	400 mm
Width	400 mm
Body material	Self-extinguishing thermoplastic
Colour housing	White
Protection grade IP	IP65
Protection grade IK	IK08

Certifications and norms

-, EN 60598-2-22:2014 + AC:2015 + AC:2016-05 + AC:2016-09 + A1:2020