



Full Moon Ring CCT

FULL MOON RING IP65 HE 26W CCT



Order code 75372

EAN 8002219906458

Technical specifications

Absorbed Power	26 W
Supply voltage type	AC
Nominal voltage (AC)	230 Vac
Ambient temperature (min)	-10 °C
Ambient temperature (max)	45 °C
Insulation class	II
CCT light tone	3000 K, 4000 K, 6500 K
CCT (max)	6500 K
CCT (min)	3000 K
Photobiological risk	RG0
CRI color rendering	>80
Diameter	300 mm
Efficiency	100 lm/W
Frequency (max)	60 Hz
Frequency (min)	50 Hz
Power factor	0.9
Luminaire flux	2600 lm
Luminous flux L70B10	57000 h
Luminous flux L70B50	100000 h
Luminous flux L80B10	36000 h
Luminous flux L80B20	50000 h
Luminous flux L80B50	49600 h
Luminous flux L90B10	20000 h
Luminous flux L90B50	23600 h
Voltage supply range (max)	240 V
Voltage supply range (min)	220 V

Mechanical specifications

Height	55 mm
Length	300 mm
Width	300 mm
Protection grade IP	IP65
Protection grade IK	IK08

Certifications and norms

-, EN 60598-2-22:2014 + AC:2015 + AC:2016-05 + AC:2016-09 + A1:2020