



RegLED CCT

REGLED CCT 10W 873MM I

Reglette LED downlight with variable light colour warm, white, cold



Order code 74077

EAN 8002219743879

Technical specifications

Absorbed Power	10 W
Supply voltage type	AC
Nominal voltage (AC)	230 Vac
Ambient temperature (min)	-20 °C
Ambient temperature (max)	40 °C
Insulation class	II
CCT light tone	3000 K, 4000 K, 5000 K
Colour consistency	SDCM3
CRI color rendering	>80
Ballast	For constant current LED
Efficiency	95 lm/W
Frequency (max)	60 Hz
Frequency (min)	50 Hz
Glow wire strength	850 °C - 30s.
Luminaire flux	950 lm
Luminous flux L70B10	71000 h
Luminous flux L70B50	100000 h
Luminous flux L80B10	45000 h
Luminous flux L80B20	50000 h
Luminous flux L80B50	62000 h
Luminous flux L90B10	25000 h
Luminous flux L90B50	29500 h
Voltage supply range (max)	265 V
Voltage supply range (min)	180 V


Installation and applications

Environment	Offices
Application	Shelves, Shops


Mechanical specifications

Height	30 mm
Length	873 mm
Width	22 mm
Weight	0.21 Kg
Colour housing	White
Protection grade IP	IP40
Protection grade IK	IK05

Certifications and norms



UK SI 2021 No. 1095, EN 62471:2008, EN IEC 60598-1:2021, EN 60598-2-1:1989, EN IEC 63000:2018, EN 62493:2010, EN 61000-3-3:2013, REG. 2019/2020(EU), EN IEC 55015:2019 + A11:2020, EN IEC 61000-3-2 :2019



Supplied accessories



424020003
CAVO STD FILA CONTINUA
REGLED



424020004
GR ACCESSORY RGL LEDECO



424020006
CAVO STD ALIMENTAZIONE
REGLED

Accessories



424020009
CONNECTION PLUG 2MT RGL
LEDECO



424020005
CONN PLUG 1.5MT RGL
LEDECO