



Stagna Easy LED

STAGNA EASY CCT IP65 60CM 20W

Compact CCT LED ceiling light with IP65 waterproof rating, with diffusing opaline screen made of polycarbonate. Calibrated heads attached to the central body and internal terminal block for quick installation.

Order code 75460

EAN 8002219895462

Technical specifications

| | |
|----------------------------|---------------------------------|
| Absorbed Power | 20 W |
| Supply voltage type | AC |
| Nominal voltage (AC) | 230 Vac |
| Ambient temperature (min) | -20 °C |
| Ambient temperature (max) | 40 °C |
| Insulation class | II |
| CCT light tone | 3000 K, 4000 K, 6500 K |
| LED number | 90 |
| Colour consistency | SDCM2 |
| CRI color rendering | >80 |
| Ballast | For constant current LED |
| Efficiency | 110 lm/W |
| Equivalent power | 2x18w |
| Frequency (max) | 60 Hz |
| Frequency (min) | 50 Hz |
| Power factor | 0.9 |
| Glow wire strength | 550 °C - 30s. |
| MTBF driver | 35000 h |
| Luminaire flux | 2200 lm |
| Luminous flux L70B50 | 50000 h |
| Mounting | Ceiling |
| Voltage supply range (max) | 240 V |
| Voltage supply range (min) | 220 V |

Installation and applications

| | |
|-------------|--|
| Environment | Secondary Areas |
| Application | Offices, Production, Warehouses |

Mechanical specifications

| | |
|---------------------|-------------------|
| Height | 74 mm |
| Length | 600 mm |
| Width | 61 mm |
| Weight | 0.9 Kg |
| Colour housing | Light Grey |
| Protection grade IP | IP65 |
| Protection grade IK | IK08 |

Certifications and norms



UK SI 2021 No. 1095, EN 62471:2008, EN
IEC 60598-1:2021, EN 60598-2-1:1989, EN
IEC 63000:2018, EN 62493:2010, EN
61000-3-3:2013, REG. 2019/2020(EU), EN
IEC 55015:2019 + A11:2020, EN IEC 61000-
3-2 :2019

Accessories



201954000
KIT 2 GANCI SOSPEN ST EASY
LED