

# Ticinque LED

## LED Emergency




**1250  
lumen**

### GENERAL CHARACTERISTICS

- Power \*** 18, 24 W
- Power supply** 230Vac ± 10% 50Hz
- Operation** Permanent (SA), Non permanent (SE)
- Standard** EN 60598-1, EN 60598-2-22, UNI EN 1838
- Protection grade** IP65, IP42
- Autonomy** 1, 2, 3h - 8h (model 18W)
- Working temp.** 0 ÷ +40 °C
- Working temp.** 0°C ÷ +40°C
- Installazione** wall, ceiling
- Housing** White Polycarbonate RAL 9003
- Optics** Symmetrical, white
- Louvre** Transparent polycarbonate
- Light source** LED

\* Indicative power for comparison with fluorescent tube fixtures



Power * W	• Dimensions (mm) •			DV diffuser
	L	B	H	
18	549	147	43	25 m

\* Indicative power for comparison with fluorescent tube fixtures

## Accessories

supplied

Order code	Description
-	no. 3 IP PLUG MEMBRANES PRE-MOUNTED ON THREE EXITS (HIGH, RIGHT, LEFT)
-	no. 1 INVISIBLE CONNECTOR COMPLETE WITH IP PLUG MEMBRANE

## Accessories

to be ordered separately

Order code	Description
<b>11582</b>	ADES EXIT TICINQUE LED
<b>11583</b>	ADES LEFT TICINQUE LED
<b>11584</b>	ADES RIGHT TICINQUE LED
<b>11585</b>	ADES DOWN TICINQUE LED




**CUNEIFORM DOUBLE REFLECTOR WITH LED SIGNAL**

### CEILING MOUNTING



### WALL MOUNTING



### CABLE GLAND



- CABLE GLAND PG16/PG20

supplied

### CABLE GROMMETS



- 3 IP CABLE GROMMETS

supplied

### SAFETY SIGNALING (Visibility Distance VD in table)



- LABELS IN ACCESSORIES TABLE

to be ordered separately

## TR Granluce

Traditional

W	Order code	Description	Model	Autonomy	Battery	N° LED	Average Flux SE lm	Average Flux SA lm	Power consump. max W	Weight kg	Pack single
24	<b>8590</b>	GRANLUCE T5LED IP65 SE2H	SE	2h	PB 6V 4Ah	32	800		5	2	1/6
24	<b>8591</b>	GRANLUCE T5LED IP65 SA2H	SA	2h	PB 6V 4Ah	32	800	180	5/8	2	1/6

## TR

Traditional **IP42**

W	Order code	Description	Model	Autonomy	Battery	N° LED	Average Flux SE lm	Average Flux SA lm	Power consump. max W	Weight kg	Pack single
18	<b>8584</b>	TICINQUE IP42 LED 18WSE8P	SE	8h	PB 6V 4Ah	32	260		2	1.8	1/6
18	<b>8585</b>	TICINQUE IP42 LED 18WSA8P	SA	8h	PB 6V 4Ah	32	260	180	2/4	1.8	1/6

## TR

Traditional **IP65**

W	Order code	Description	Model	Autonomy	Battery	N° LED	Average Flux SE lm	Average Flux SA lm	Power consump. max W	Weight kg	Pack single
18	<b>8586</b>	TICINQUE IP65 LED 18WSE8P	SE	8h	PB 6V 4Ah	32	260		2	1.8	1/6
18	<b>8587</b>	TICINQUE IP65 LED 18WSA8P	SA	8h	PB 6V 4Ah	32	260	180	2/4	1.8	1/6

## AT Granluce

Autotest

W	Order code	Description	Model	Autonomy	Battery	N° LED	Average Flux SE lm	Average Flux SA lm	Power consump. max W	Weight kg	Pack single
24	<b>8592</b>	GRANLUCE T5LED AT IP65 SE123H	SE	1-2-3h	PB 6V 4Ah	32	1250/800/550		5	2	1/6
24	<b>8593</b>	GRANLUCE T5LED AT IP65 SA123H	SA	1-2-3h	PB 6V 4Ah	32	1250/800/550	400	5/15	2	1/6