



Acciaio LED 1.5m / Stainless steel

Industrial LED luminaires



Material:

- body: steel sheet finished by powder technology varnishing or stainless steel (version SG)
- end caps: die-cast aluminium with central screw fixing system
- color: gray RAL 7035
- reflector: polished aluminium sheet
- diffuser: special glass or frosted opal

Ambient temperature: -20 ÷ 30°C

Degree of protection: IP66

Rated voltage: 230 V/50 Hz

Control gear: LED driver, dimmable DALI driver on request
the luminaires are offered also in emergency version

Mounting: surfaced on ceiling or wall
(endings are components of the luminaire)

Application: industrial premises, storehouses, production lines, garages, factory halls, farms

MTBF of power supply** 65 000 h
(MTBF: Mean Time Between Failures)

Luminous flux decrease:** > 50 000 h (L80B20)
Color temp. stability: 3 SDCM

** Applies to ambient temperature 25°C

Power* W	Code	Article	Absorption W	Lum. flux (lm)	lm/W	Color temp. K	Ra	EEC	L x B x H (mm)	Kg	Description
2x80	A280TD	Acciaio LED DIFF	80	8 300	104	4 000	>80	A+	1 500 x 170 x 88	5.5	wide-beam reflector
2x80	A280TDP	Acciaio LED DIFF	80	8 300	104	4 000	>80	A+	1 500 x 170 x 88	5.5	through wiring 5x 1.5mm

DALI dimmable version for A280TD and A280TDP on request (please add DL at the end of ordering code).

* Indicative power just for fluorescent fixtures comparison purpose

Stainless steel versions

Power* W	Code	Article	Absorption W	Lum. flux (lm)	lm/W	Color temp. K	Ra	EEC	L x B x H (mm)	Kg	Description
2x80	A280TD/SG	Acciaio LED DIFF	80	8 300	104	4 000	>80	A+	1 500 x 170 x 88	5.5	wide-beam reflector
2x80	A280TDP/SG	Acciaio LED DIFF	80	8 300	104	4 000	>80	A+	1 500 x 170 x 88	5.5	through wiring 5x 1.5mm

DALI dimmable version for A280TD/SG and A280TDP/SG on request (please add DL as follows: A280TDDL/SG and A280TDPDL/SG).

* Indicative power just for fluorescent fixtures comparison purpose

A280TDM and A80TDM/SG with frosted opal diffuser on request.