


REGLETTE T5



Reglette T5 is a fluorescent batten for wall, suspension and ceiling installation, even if mounted in direct contact with flammable surfaces (furniture included). The connection to mains is done through a connector on the head. It is possible to link up to 12 luminaires in a single row thanks to the integrated through wiring system.

Every fixture has an on-board switch and is supplied with power cables and continuous row installation head-to-head connector.



GENERAL SPECIFICATION

Power	6, 8, 14, 21, 28, 35 W
Supply	220/240 VAC - 50/60 Hz
Conformity to	EN60598-1; EN60598-2-1; CE
Protection degree	IP30
Ambient temp.	-15°C +40°C
Mounting	Different types of installation are possible thanks to the brackets supplied with the fixture
Body	White RAL2003 polycarbonate self extinguishing
Screen	PMMA opal
Power supply	Integrated, Electronic

Power W	• Dimension (mm) •			Lamp	Weight kg
	L	B	H		
6	269	28	43	T5	-
8	345	28	43	T5	-
14	606	28	43	T5	-
21	905	28	43	T5	-
28	1205	28	43	T5	-
35	1505	28	43	T5	-

ACCESSORIES - Supplied with

Part #	Description	Packaging
-	150mm connection cable	1
-	Adaptor for continuous row	1
•	2 mounting brackets	1
•	Power cable	1

ACCESSORIES - to be ordered separately

Part #	Description	Packaging
74025	400mm connection cable	1

MULTIFUNCTION CONNECTION: TO THE POWER MAINS OR TO ANOTHER FIXTURE



Quick connection system with integrated power supply and continuous row wires: in case of multiple fixtures (even of different length) the power supply is provided by one single wire. Every fixture can be switched on and off independently from the others.

A COUNTINUOUS LINE OF LIGHT



Perfect mechanical union without any length increase. The connector is completely integrated in the fixtures allowing a perfect matching of the parts.

REGLETTE T5

WITH INTEGRATED SWITCH

W	Part #	Description	EAN code	Power W	Colour temp.	Ra	N° LED	Flux (lm)	Lighting efficiency (lm/W)	Energy class	Packaging single/multi
6	74006	RGL 6 T5 G5 3000K	8002219589729	5	3000K	FD 6W T5	G5	200	40	A	1/30
6	74000	RGL 6 T5 G5 4000K	8002219585189	5	4000K	FD 6W T5	G5	200	40	A	1/30
6	74018	RGL 6 T5 G5 6500K	8002219594105	5	6500K	FD 6W T5	G5	200	40	A	1/30
8	74007	RGL 8 T5 G5 3000K	8002219589736	7,5	3000K	FD 8W T5	G5	273	36	A	1/30
8	74001	RGL 8 T5 G5 4000K	8002219585196	7,5	4000K	FD 8W T5	G5	273	36	A	1/30
8	74019	RGL 8 T5 G5 6500K	8002219594112	7,5	6500K	FD 8W T5	G5	273	36	A	1/30
14	74008	RGL 14 T5 G5 3000K	8002219589743	13,5	3000K	FD 14W T5	G5	1030	76	A+	1/30
14	74002	RGL 14 T5 G5 4000K	8002219585202	13,5	4000K	FD 14W T5	G5	1030	76	A+	1/30
14	74020	RGL 14 T5 G5 6500K	8002219594129	13,5	6500K	FD 14W T5	G5	1030	76	A+	1/30
21	74009	RGL 21 T5 G5 3000K	8002219589750	20,5	3000K	FD 21W T5	G5	1735	85	A+	1/20
21	74003	RGL 21 T5 G5 4000K	8002219585219	20,5	4000K	FD 21W T5	G5	1735	85	A+	1/20
21	74021	RGL 21 T5 G5 6500K	8002219594136	20,5	6500K	FD 21W T5	G5	1735	85	A+	1/20
28	74010	RGL 28 T5 G5 3000K	8002219589767	27	3000K	FD 28W T5	G5	2160	80	A+	1/20
28	74004	RGL 28 T5 G5 4000K	8002219585226	27	4000K	FD 28W T5	G5	2160	80	A+	1/20
28	74022	RGL 28 T5 G5 6500K	8002219594143	27	6500K	FD 28W T5	G5	2160	80	A+	1/20
35	74011	RGL 35 T5 G5 3000K	8002219589774	34,5	3000K	FD 35W T5	G5	2730	79	A+	1/20
35	74005	RGL 35 T5 G5 4000K	8002219585233	34,5	4000K	FD 35W T5	G5	2730	79	A+	1/20
35	74023	RGL 35 T5 G5 6500K	8002219594150	34,5	6500K	FD 35W T5	G5	2730	79	A+	1/20

