



Rondo LED

Ceiling and suspended LED luminaires



Material:

- body: painted steel sheet
- color: grey (RAL 9006)
- diffuser: frosted acrylic or microprismatic optics

Ambient temperature: $-20 \div 25^{\circ}\text{C}$

Degree of protection: IP20

Rated voltage: 230 V/50 Hz

Control gear: LED driver, the luminaires are offered also in emergency version

Mounting: surfaced or suspended on ceiling

Accessories: (to be ordered separately)

99-0157 – wire suspensions, transparent power cable $3 \times 0.75 \text{ mm}^2$ (120 cm) – set for one luminaire

99-0158 – wire suspensions, transparent power cable $5 \times 0.75 \text{ mm}^2$ (120 cm) – set for one luminaire

99-0159 – wire suspensions, transparent power cable $7 \times 0.75 \text{ mm}^2$ (120 cm) – set for one luminaire

Application: shops, stairways, corridors in shopping centers, vestibules, hotels and restaurants

Code	Optics	Absorption W	Lum. flux (lm)	lm/W	Color temp. K	Ra	EEC	L x B (mm)	Kg
A17-10061CM	frosted diffuser	36	3 300	92	4 000	>80	A+	352 x 79	3.0
A17-10061CW	micro-prism optic system	36	3 200	89	4 000	>80	A+	352 x 79	3.0